

443 Skywalker HD o-Curve™ ESD

Skywalker HD o-Curve™ ESD 22.5-degree bubble mat.



Ergonomic, Anti-fatigue & Safety Matting - ESD Matting & Accessories

443 Skywalker HD o-Curve™ ESD

The Skywalker HD™ accessories maintain the same feel as the Skywalker HD™ mats with an ergonomic bubble pattern and matching rubber compounds. This seamless integration allows for unlimited configuration possibilities.

- Slip resistance rating R9 according to DIN 51130
- Static dissipative natural rubber compound
- Meets IEC61340-4-1 (category DIF), measured resistance Rg 106 - 109 Ω, Rp 106 - 109 Ω

Recommended use

- Dry Areas
- For placement in ESD assembly lines, picking, packing and logistics warehouses, individual work stations.
- Heavy duty

Colors:

- Black

Sizes:

- 91cm x 22.5 deg

Accessories:

- 825-C
- 441 SkywalkerHD o-Curve™ Safety Ramp Nitrile
- 469 Skywalker HD Safety Line™
- 051 ESD Floor Grounding Cord
- 481 Skymaster® Hd O-Curve™ Ramp

Ergonomic, Anti-fatigue & Safety Matting - ESD Matting & Accessories

Skywalker HD o-Curve™ ESD

General

Brand	Notrax
Category	ESD Matting & Accessories
Product Number	443
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Skywalker HD o-Curve™ ESD
Recommended use	For placement in ESD assembly lines, picking, packing and logistics warehouses, individual work stations.
Series	Skywalker HD™
Shipping Location	Barendrecht 2992SB, The Netherlands, Chicago, IL 60638, United States
Type	Accessories - Skywalker HD™
Update trigger	20210310-1301
Usage Intensity	Heavy duty

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Reach US	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Sustainability	Recyclable material
Warranty	1

Tests

Abrasion Resistance 1000	0.824
Elongation	210%
ESD Rg	Rp 10 ⁶ - 10 ⁹ Ω
ESD Rp	Rg 10 ⁶ - 10 ⁹ Ω
Fire rating US	Pass
Hardness	67 Shore A
Slip Rating	R9
Surface Flammability	Pass
Tear Strength	10.5 N/mm

Technical Specifications

Application	Industrial Environments
Breaking Load	4.80 Mpa
Edges	Attachable bevelled edges are available
Material	Static dissipative natural rubber
Material Group	Rubber
Process	Compression Moulding

Skywalker HD o-Curve™ ESD Black

Art. nr.	Dimension (cm)	Weight (kg)	Height (cm)
443SC045BL	91cm x 22.5 deg	6.4	1.3

Accessories

825-C 441 SkywalkerHD o-Curve™ Safety Ramp Nitrile 469 Skywalker HD Safety Line™ 051 ESD Floor Grounding Cord

481 Skymaster® Hd O-Curve™ Ramp