

380 Swisslon XT™

Premium quality barrier matting



Dust Control Matting - Indoor Contract & Installation Matting

380 Swisslon XT™

Premium quality barrier matting designed to remove walked-in moisture and finer dirt particles in large indoor entrance areas, including wall-to-wall applications.

- Great ability to retain moisture (>5.8 litres per m²)
- The new tri-colour grit pattern provides outstanding dirt-hiding characteristics

Recommended use

- Indoor
- For placement in recessed matwell frames (depth 7 mm) or wall-to-wall installations in larger entrances at hotels, shopping malls, cinemas, public buildings, department stores, banks, restaurants and on stairs
- Heavy traffic

Colors:

- Charcoal
- Granite
- Grey
- Mocha

Sizes:

- 120cm x 180cm
- 120cm x 240cm
- 60cm x 90cm
- 90cm x 120cm
- 90cm x 150cm
- 135cm x linm
- 200cm x linm
- 135cm x 20m
- 200cm x 20m

Accessories:

- 083 Bevelled Nosing 2 mm

WATER RETENTION

CRUSH RESISTANCE

RATING DUST CONTROL

Dust Control Matting - Indoor Contract & Installation Matting

Swisslon XT™

General

Brand	Notrax
Category	Indoor Contract & Installation Matting
Product Number	380
Product Family	Industrial & Commercial Matting
Product Group	Dust Control Matting
Product Name	Swisslon XT™
Recommended use	For placement in recessed matwell frames (depth 7 mm) or wall-to-wall installations in larger entrances at hotels, shopping malls, cinemas, public buildings, department stores, banks, restaurants and on stairs
Shipping Location	Barendrecht 2992SB, The Netherlands
Type	Indoor – Contract and Installation Matting
Update trigger	20210310-1301
Usage Intensity	Heavy traffic

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Sustainability	Contributes to a cleaner environment by reducing need of cleaning chemicals
Warranty	1

Tests

Comfort Class	LC2
Fire rating EU	En 13501-1 Cfl-S1
Fire rating US	Pass
Light Fastness	6
Organic Solvents	4
Rubbing Fastness	4
Salt Water	4
Shampoo	4
Static Charge	<0.1
Surface Flammability	Pass
Water Fastness	4

Technical Specifications

Absorption Capacity	6
Backing	Black vinyl (DOP free)
Dimensional Stability	<0.4
Edges	Vinyl borders: 2.5 cm on both sides
Material	100% polyamide 6.0 yarns
Material Group	Polyamide
Pile Weight (g)	850
Process	Tufting
Tufts	85500
Yarn Construction	Cut loop pile - velours

Swisslon XT™ Grey

Art. nr.	Dimension (cm)	Weight (kg)	Height (cm)	Recommended accessories
380S0023GY	60cm x 90cm	2.3	0.9	
380S0046GY	120cm x 180cm	7.9	0.9	
380S0035GY	90cm x 150cm	4.9	0.9	
380S0048GY	120cm x 240cm	10.5	0.9	
380R0051GY	135cm x 20m	94.6	0.9	
380C0078GY	200cm x linm	7.3	0.9	083N0000BL
380R0078GY	200cm x 20m	145.6	0.9	
380C0051GY	135cm x linm	4.73	0.9	083N0000BL
380S0034GY	90cm x 120cm	3.9	0.9	

Swisslon XT™ Charcoal

Art. nr.	Dimension (cm)	Weight (kg)	Height (cm)	Recommended accessories
380S0048CH	120cm x 240cm	10.5	0.9	
380S0023CH	60cm x 90cm	2.3	0.9	
380S0046CH	120cm x 180cm	7.9	0.9	
380R0051CH	135cm x 20m	94.6	0.9	
380S0035CH	90cm x 150cm	4.9	0.9	
380C0078CH	200cm x linm	7.3	0.9	083N0000BL
380R0078CH	200cm x 20m	145.6	0.9	
380C0051CH	135cm x linm	4.73	0.9	083N0000BL
380S0034CH	90cm x 120cm	3.9	0.9	

Swisslon XT™ Granite

Art. nr.	Dimension (cm)	Weight (kg)	Height (cm)	Recommended accessories
380S0048GT	120cm x 240cm	10.5	0.9	
380S0023GT	60cm x 90cm	2.3	0.9	
380S0035GT	90cm x 150cm	4.9	0.9	
380S0046GT	120cm x 180cm	7.9	0.9	
380R0051GT	135cm x 20m	94.6	0.9	
380C0078GT	200cm x linm	7.3	0.9	083N0000BL
380R0078GT	200cm x 20m	145.6	0.9	
380C0051GT	135cm x linm	4.73	0.9	083N0000BL
380S0034GT	90cm x 120cm	3.9	0.9	

Swisslon XT™ Mocha

Art. nr.	Dimension (cm)	Weight (kg)	Height (cm)	Recommended accessories
380S0048BR	120cm x 240cm	10.5	0.9	
380S0023BR	60cm x 90cm	2.3	0.9	
380S0046BR	120cm x 180cm	7.9	0.9	
380S0035BR	90cm x 150cm	4.9	0.9	
380C0078BR	200cm x linm	7.3	0.9	083N0000BL
380C0051BR	135cm x linm	4.73	0.9	083N0000BL
380S0034BR	90cm x 120cm	3.9	0.9	

Accessories

083 Bevelled Nosing 2
mm