# 573 De-Flex™ ESD

ESD modular mat with dual locking connection



# Ergonomic, Anti-fatigue & Safety Matting - ESD Matting & Accessories 573 De-Flex™ ESD

Extremely comfortable heavy duty anti-fatigue matting system with popular diamond plate traction surface that can be easily assembled for coverage of large areas or individual workstation mats.

- Modular rubber tiles are designed with a universal double-locking system on all sides to ensure an extra strong yet seamless connection for fast installation
- The 19 mm thick platform insulates the worker from the hard ground while the bulleted domes underneath allow the mat to bend and flex with every movement
- Unique extended ramp prevents tripping and allows cart access with smart bevelling solutions for inside and outside corners

#### Recommended use

- Dry Areas
- For placement in ESD assembly lines, picking, packing and logistics warehouses, individual work stations.
- Heavy duty

### Colors:

Black

### Sizes:

- 45cm x 45cm
- 45cm x 45cm

### Accessories:

- 825-C
- 051 ESD Floor Grounding Cord
- 571 De-Flex™ Safety Ramp Nitrile



# Ergonomic, Anti-fatigue & Safety Matting - ESD Matting & Accessories $De\text{-Flex}^{\text{TM}}$ ESD

### General

Brand	Notrax		
Category	ESD Matting & Accessories		
Product Number	573		
Product Family	Industrial & Commercial Matting		
Product Group	Ergonomic, Anti-fatigue & Safety Matting		
Product Name	De-Flex™ ESD		
Recommended use	For placement in ESD assembly lines, picking, packing and logistics warehouses, individual work stations.		
Series	De-Flex®		
Shipping Location	Barendrecht 2992SB, The Netherlands, Chicago, IL 60638, United States		
Туре	Dry Areas - Heavy Duty Modular Rubber Mats		
Update trigger	20210310-1301		
Usage Intensity	Heavy duty		

## Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).	
Reach US	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).	
Rohs US	Rohs compliant (Restriction of Hazardous Substances).	
Warranty	1	

## Tests

Fire rating US	Pass
Slip Rating	R10

## **Technical Specifications**

Application	Industrial Environments	
Edges	Attachable bevelled edges are available	
Material	Static dissipative natural rubber	
Material Group	Rubber	
Process	Compression Moulding	

## De-Flex™ ESD Black

573S1818BL 573B1818BL

Art. nr.	Dimension (cm)	Weight (kg)	Height (cm)
573S1818BL	45cm x 45cm	3.3	1.9
573B1818BL	45cm x 45cm	26.4	1.9

# Accessories 825-C

051 ESD Floor Grounding 571 De-Flex<sup>™</sup> Safety Cord Ramp Nitrile