

# 649 Safety Stance Solid™

High quality anti-fatigue matting



# Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting

## 649 Safety Stance Solid™

High quality anti-fatigue matting for heavy duty industrial environments. Unique DiamondGrid™ surface pattern ensures sure footing to prevent slips and falls while channels drain incidental oil exposure.

- Closed design ensures easy cleaning and prevents small items from falling under the mat
- Ergonomic benefit derived from 20 mm thick resilient worker platform
- Highly visible nitrile rubber orange coloured borders included on 3 sides for added safety
- Made of 100% nitrile rubber compound designed to withstand industrial oils and harsh chemicals



### Recommended use


- Dry Areas
- For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
- Heavy duty

### Colors:

- Black
- Black/Orange

### Sizes:

- 66cm x 102cm
- 90cm x 150cm
- 97cm x 163cm
- 97cm x 315cm
- per m2



### Accessories:

- 549K Safety Stance™ Connectors Black
- 549N Safety Stance™ Ramps Nitrile 5 mm
- INS INSTALLATION

WEAR RESISTANCE

SLIP RESISTANCE

ANTI-FATIGUE



# Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting

## Safety Stance Solid™

### General

Brand	Notrax
Category	Dry Areas Modular Matting
Product Number	649
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Safety Stance Solid™
Recommended use	For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
Shipping Location	Barendrecht 2992SB, The Netherlands
Type	Dry Areas - Heavy Duty Nitrile Mats
Update trigger	20210310-1301
Usage Intensity	Heavy duty

### Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Warranty	1

### Tests

Abrasion Resistance 1000	3.1%
Elongation	258.2%
Foam Battery	40 lb/in <sup>2</sup>
Hardness	33 Shore A
Slip Rating	R10
Coefficient Friction Dry	0.65
Surface Flammability	Pass

### Technical Specifications

Application	Industrial Environments
Edges	Orange coloured borders included on 3 sides
Material	100% Nitrile rubber
Material Group	Nitrile rubber
Process	Compression Moulding

## Safety Stance Solid™ Orange/Black

Art. nr.	Dimension (cm)	Weight (kg)	Height (cm)
649S0000BL	per m2	15	2
649S2640OB	66cm x 102cm	10.4	2
649S3864OB	97cm x 163cm	24.7	2
649S3124OB	97cm x 315cm	43.74	2

## Safety Stance Solid™ Black - No Bevels

Art. nr.	Dimension (cm)	Weight (kg)	Height (cm)
649S0035BL	90cm x 150cm	20.25	2

## Accessories

549K Safety Stance™ Connectors Black	549N Safety Stance™ Ramps Nitrile 5 mm	INS INSTALLATION
---	---	------------------

Technical Drawings  
Safety Stance Solid™