

465 Skywalker HD™ Nitrile FR

Nitrile FR rubber tiles with a bubble pattern



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting

465 Skywalker HD™ Nitrile FR

Heavy duty rubber tiles can be easily assembled for coverage of large areas or individual workstations. Ergonomic benefit derived from a 13 mm thick worker platform with a bubble pattern for maximum fatigue relief in dry industrial environments.

- The unique design and craftsmanship make the mat easy to handle and easy to install on site
- A tooled grid of 30 cm x 30 cm sections on the underside of the mat makes further customization quick and easy
- Attachable bevelled edges prevent tripping and allow inside and outside corners
- Resistant to most industrial oils and suitable for welding areas

Recommended use

- Dry Areas
- For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
- Heavy duty

Colors:

- Black

Sizes:

- 91cm x 91cm
- per m2

Accessories:

- INS INSTALLATION
- 469 Skywalker HD Safety Line™
- 461 SkywalkerHD™ Safety Ramp Nitrile

Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting Skywalker HD™ Nitrile FR

General

Brand	Notrax
Category	Dry Areas Modular Matting
Product Number	465
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Skywalker HD™ Nitrile FR
Recommended use	For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
Series	Skywalker HD™
Shipping Location	Chicago, IL 60638, United States, Barendrecht 2992SB, The Netherlands
Type	Dry Areas - Modular Systems
Update trigger	20210310-1301
Usage Intensity	Heavy duty

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Reach US	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Sustainability	Recyclable material
US Warranty	7
Warranty	1

Tests

Abrasion Resistance 1000	0.739
Elongation	240%
Fire rating EU	EN 13501-1 Bfl-S1
Fire rating US	Pass
Hardness	68 Shore A
Slip Rating	R9
Surface Flammability	Pass
Tear Strength	19.53 N/mm

Technical Specifications

Application	Industrial Environments
Breaking Load	5.50 Mpa
Edges	Attachable bevelled edges are available
Material	100% nitrile fire retardant rubber compound
Material Group	Nitrile rubber
Process	Compression Moulding

Skywalker HD™ Nitrile FR Black

Art. nr.	Dimension (cm)	Weight (kg)	Height (cm)
465S0033BL	91cm x 91cm	10.5	1.3
465S0000BL	per m2	12.3	1.3

Accessories

INS INSTALLATION 469 Skywalker HD Safety Line™ 461 SkywalkerHD™ Safety Ramp Nitrile