

# 656S Cushion Ease Solid™ Nitrile

Heavy duty modular rubber tiles



# Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting 656S Cushion Ease Solid™ Nitrile

Ergonomic benefit derived from a 19 mm thick worker platform with a closed anti-slip pebble structure surface for maximum anti-fatigue comfort in dry industrial environments.

- Heavy duty rubber tiles can be easily assembled for coverage of large areas or individual workstations, wall-to-wall or as islands
- Resistant to most industrial oils
- Compatible with patented MD Ramp System™ for smart safety bevelling solutions; allows outside and inside corners

#### Recommended use

- Wet/Dry and Oily Areas
- For placement in manufacturing plants, production lines, assembly lines, CNC machines, metal working for individual workstations and custom work platforms
- Heavy duty

#### Colors:

- 5S Grey
- Black

#### Sizes:

- 91cm x 91cm
- per m<sup>2</sup>

#### Accessories:

- 552 MD-X Ramp System™ Nitrile
- INS INSTALLATION
- 651 M.D. Fire Retardent Ramp System
- 551 MD Ramp System™ Nitrile



WEAR RESISTANCE

SLIP RESISTANCE

ANTI-FATIGUE

# Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting Cushion Ease Solid™ Nitrile

## General

Brand	Notrax
Category	Dry Areas Modular Matting
Product Number	656S
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Cushion Ease Solid™ Nitrile
Recommended use	For placement in manufacturing plants, production lines, assembly lines, CNC machines, metal working for individual workstations and custom work platforms
Series	Cushion-Ease®
Shipping Location	Chicago, IL 60638, United States, Barendrecht 2992SB, The Netherlands
Type	Dry Areas - Heavy Duty Modular Rubber Mats
Update trigger	20210310-1301
Usage Intensity	Heavy duty

## Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Reach US	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Sustainability	Recyclable material
Warranty	1

## Tests

Abrasion Resistance 1000	1.50% weight loss (5000 cycles)
Compression Deflection 1.4	37.0 lb/in <sup>2</sup> (at 25%)
Compression Deflection 2.8	98.9 lb/in <sup>2</sup> (at 50%)
Fire rating US	Pass
Hardness	64 Shore A
Slip Rating	R9
Coefficient Friction Dry	0.88
Surface Flammability	Pass

## Technical Specifications

Application	Industrial Environments
Edges	Attachable bevelled edges are available
Material	100% Nitrile rubber
Material Group	Nitrile rubber
Process	Compression Moulding

# Cushion Ease Solid™ Nitrile Grey

656S0000GY

656S0033GY

Art. nr.	Dimension (cm)	Weight (kg)	Height (cm)
656S0000GY	per m2	13.6	1.9
656S0033GY	91cm x 91cm	12	1.9

# Cushion Ease Solid™ Nitrile Black

Art. nr.	Dimension (cm)	Weight (kg)	Height (cm)
656S0000BL	per m2	13.6	1.9
656S0033BL	91cm x 91cm	12	1.9

## Accessories

INS INSTALLATION

651 M.D. Fire Retardent  
Ramp System

551 MD Ramp System™  
Nitrile

552 MD-X Ramp  
System™ Nitrile