

# 826 Diamond Stat™

Static dissipative anti-fatigue mat



# Ergonomic, Anti-fatigue & Safety Matting - ESD Matting & Accessories

## 826 Diamond Stat™

Ergonomic benefit derived from 14 mm thick worker platform of a static dissipative combination of tough top surface laminated onto a comfortable sponge base for maximum durability coupled with fatigue relief.

- Featured with RedStop™ slip resistant backing to prevent mats from shifting
- UniFusion™ technology, engineered to resist in the harshest work environments
- Diamond deck plate surface provides traction and allows easy twist turns
- Equipped with 10 mm female socket attached to the mat and grounding cord
- Bevelled edges on all four sides to minimize the risk of tripping

### Recommended use

- Dry Areas
- For placement in ESD assembly lines, picking, packing and logistics warehouses, individual work stations.
- Heavy duty

### Colors:

- Black

### Sizes:

- 60cm x 91cm
- 91cm x 150cm
- 91cm x 200cm
- 91cm x 300cm
- 122cm x linm
- 91cm x linm
- 122cm x 22.8m
- 91cm x 22.8m

### Accessories:

- 825-C
- 051 ESD Floor Grounding Cord

# Ergonomic, Anti-fatigue & Safety Matting - ESD Matting & Accessories

## Diamond Stat™

### General

Brand	Notrax
Category	ESD Matting & Accessories
Product Number	826
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Diamond Stat™
Recommended use	For placement in ESD assembly lines, picking, packing and logistics warehouses, individual work stations.
Shipping Location	Barendrecht 2992SB, The Netherlands, Moselle, MS 39459, United States
Type	Dry Areas - Conductive Mats
Update trigger	20210310-1301
Usage Intensity	Heavy duty

### Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Reach US	Not REACH Compliant
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Sustainability	100% recycled PVC top surface
US Warranty	3
Warranty	1

### Tests

Fire rating EU	En 13501-1 Cfl-S1
Fire rating US	Pass
Slip Rating	R10
Coefficient Friction Dry	0.81
Surface Flammability	Pass

### Technical Specifications

Application	Dry industrial environments
Backing	Closed Cell Rubber
Chemical Resistance	Cat. V PVC
Edges	Bevelled edges on all sides
Material	Conductive PVC
Material Group	PVC
Process	Lamination

## Diamond Stat™ Black

Art. nr.	Dimension (cm)	Weight (kg)	Height (cm)
826S202MBL	91cm x 200cm	12	1.4
826S0035BL	91cm x 150cm	9	1.4
826S0023BL	60cm x 91cm	3.5	1.4
826S0312BL	91cm x 300cm	18	1.4
826C0048BL	122cm x linm	7.8	1.4
826R0375BL	91cm x 22.8m	135	1.4
826R0475BL	122cm x 22.8m	180	1.4
826C0036BL	91cm x linm	5.9	1.4

## Accessories

825-C                      051 ESD Floor Grounding  
Cord