830 Switchboard Matting™ Class 2 Class 2 insulation matting



Ergonomic, Anti-fatigue & Safety Matting - Switchboard Matting 830 Switchboard Matting™ Class 2

Insulating matting prevents workers from being "grounded" and provides safety in case of electrical shock. The corrugated saw-tooth top surface increases traction and is easy to sweep clean.

- Each square inch of matting is tested in conformance with ANSI/ASTM D-178 specifications
- The corrugated saw-tooth top surface increases traction and is easy to sweep clean
- Recommended maximum usage: 17.000 Volts.
- Must be replaced every 12 months for optimum safety

Recommended use

- Dry Areas
- Around electric sub-stations, transformers and switches, electrical panels, engine and generator rooms
- Heavy duty

Colors:

Black

Sizes:

- 90cm x 150cm
- 91cm x linm
- 91cm x 22.8m

Ergonomic, Anti-fatigue & Safety Matting - Switchboard Matting $\mathsf{Switchboard}\ \mathsf{Matting}^\mathsf{TM}\ \mathsf{Class}\ 2$

General

Brand	Notrax			
Category	Switchboard Matting			
Product Number	830			
Product Family	Industrial & Commercial Matting			
Product Group	Ergonomic, Anti-fatigue & Safety Matting			
Product Name	Switchboard Matting™ Class 2			
Recommended use	Around electric sub-stations, transformers and switches, electrical panels, engine and generator rooms			
Shipping Location	Barendrecht 2992SB, The Netherlands, Moselle, MS 39459, United States			
Туре	Industrial Specialties - Electrical Protective Matting			
Update trigger	20210310-1301			
Usage Intensity	Heavy duty			

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).	
Reach US	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals	
Rohs US	Rohs compliant (Restriction of Hazardous Substances).	
Warranty	1	

Tests

Elongation	317%
Hardness	91 Shore A
Surface Flammability	Pass
Tear Strength	2505 PI

Technical Specifications

Application	Industrial Environments		
Edges	No borders		
Material	PVC (DOP free)		
Material Group	PVC		
Process	Calendering		
Voltage Class	2		
Voltage Maximum	20000		
Voltage Recommended	17000		

Switchboard Matting™ Class 2 Black

Art. nr.	Dimension (cm)	Weight (kg)	Height (cm)
830S0035BL	90cm x 150cm	11.6	0.64
830R0375BL	91cm x 22.8m	174	0.64
830C0036BL	91cm x linm	7.6	0.64