

Printing date 16.06.2022 Version number 76 (replaces version 75) Revision: 30.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SPRING PRO FLORIST SPRAY ADHESIVE 400 ML
- · Article number: SPR057A
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category Feed materials, Intermediates
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Glue/ Sising agent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SPRING FROM HOLLAND BV

Cornelis Verolmeweg 12-14

2171 KV Sassenheim, The Netherlands

Tel: 0031 252 231651

Email: info@springfromholland.nl

- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

+31 (0)252-231651 (08:00h - 15:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Version number 76 (replaces version 75) Printing date 16.06.2022 Revision: 30.03.2022

Trade name: SPRING PRO FLORIST SPRAY ADHESIVE 400 ML

· Hazard pictograms





· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

pentane

butanone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents / container in accordance with regional regulations. P501

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

CAS: 67-64-1	acetone	25-<50%
EINECS: 200-662-2	♦ Flam. Liq. 2, H225	-1
Index number: 606-001-00-8	(Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119471330-49	EUH066	
EC number: 921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-	20-<25%
Reg.nr.: 01-2119475514-35	hexane	
	◈ Flam. Liq. 2, H225	-1
	& Asp. Tox. 1, H304	
	Aquatic Chronic 2, H411	
	Skin Irrit. 2, H315; STOT SE 3, H336	

(Contd. of page 1)

Printing date 16.06.2022 Version number 76 (replaces version 75) Revision: 30.03.2022

Trade name: SPRING PRO FLORIST SPRAY ADHESIVE 400 ML

CAS: 115-10-6	dimethyl ether	(Contd. of page 20-<25
EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	ⓑ Flam. Gas 1A, H220	
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<109
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas IA, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 109-66-0 EINECS: 203-692-4 Index number: 601-006-00-1 Reg.nr.: 01-2119459286-30	pentane	<2.5%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone ♦ Flam. Liq. 2, H225 ♦ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	<2.5%
CAS: 61790-50-9 EINECS: 263-142-4 Reg.nr.: 01-2119486885-17	Resin acids and Rosin acids, potassium salts © Eye Irrit. 2, H319	<2.5%
CAS: 78-78-4 EINECS: 201-142-8 Index number: 601-006-00-1 Reg.nr.: 01-2119475602-38	isopentane	<2.5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture

 During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

Printing date 16.06.2022 Version number 76 (replaces version 75) Revision: 30.03.2022

Trade name: SPRING PRO FLORIST SPRAY ADHESIVE 400 ML

(Contd. of page 3)

· 5.3 Advice for firefighters -

· Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- \cdot 7.3 *Specific end use*(s) *No further relevant information available.*

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

109-66-0 pentane

WEL Long-term value: 1800 mg/m³, 600 ppm

(Contd. on page 5)

Printing date 16.06.2022 *Version number 76 (replaces version 75)* Revision: 30.03.2022

Trade name: SPRING PRO FLORIST SPRAY ADHESIVE 400 ML

(Contd. of page 4)

78-93-3 butanone

WEL | Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm

Sk, BMGV

78-78-4 isopentane

WEL Long-term value: 1800 mg/m³, 600 ppm

· Ingredients with biological limit values:

78-93-3 butanone

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· Hand protection



Protective gloves

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

(Contd. on page 6)

Printing date 16.06.2022 *Version number 76 (replaces version 75)* Revision: 30.03.2022

Trade name: SPRING PRO FLORIST SPRAY ADHESIVE 400 ML

(Contd. of page 5)

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol · Colour: Whitish · Odour: Solvent-like · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

Not applicable, as aerosol. Not applicable.

· Flammability

· Lower and upper explosion limit

0.6 Vol % (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, · Lower:

cyclics, <5% n-hexane)

26.2 *Vol* % (115-10-6 dimethyl ether) · Upper:

· Flash point: Not applicable, as aerosol.

>200 °C (>392 °F) (Hydrocarbons, C6-C7, n-alkanes, · Ignition temperature:

isoalkanes, cyclics, <5% n-hexane)

· Decomposition temperature: Not determined.

Mixture is non-soluble (in water).

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic: Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C (68 °F): 4000 hPa (3000.2 mm Hg)

· Density and/or relative density

· Density at 20 °C (68 °F): $0.7 \, g/cm^3 \, (5.8 \, lbs/gal)$ · Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and

environment, and on safety.

· Explosive properties: Not determined.

· Solvent content:

· Organic solvents: 97.0 % · **VOC** (**EC**) 669.0 g/l · VOC-EU% 96.95 % · Solids content: 3.1 %

· Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard classes

· Explosives Void

(Contd. on page 7)

Version number 76 (replaces version 75) Revision: 30.03.2022 Printing date 16.06.2022

Trade name: SPRING PRO FLORIST SPRAY ADHESIVE 400 ML

	(Contd. of page 6)
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container:
	May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flamme	able
gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

Ticute toxi	· Acute toxicity		
· <i>LD/LC50</i> 1	· LD/LC50 values relevant for classification:		
67-64-1 ac	67-64-1 acetone		
Oral	LD50	5800 mg/kg (rat)	
Dermal	LD50	>15800 mg/kg (rabbit)	
Inhalative	LC50 / 4h	76 mg/l (rat)	
Hydrocarb	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	LD50	>5840 mg/kg (rat)	
Dermal	LD50	>2920 mg/kg (rab)	
Inhalative	LC50 / 4h	>25.2 mg/l (rat)	
109-66-0 р	109-66-0 pentane		
Oral	LD50	>5000 mg/kg (rat)	
Inhalative	LC50 / 4h	25.3 mg/l (rat)	
78-93-3 bu	78-93-3 butanone		
Oral	LD50	>2193 mg/kg (rat)	
Dermal	LD50	>5000 mg/kg (rabbit)	
Inhalative	LC50 / 4 h	34 mg/m3 (rat)	
. Skin corro	· Skin corrosion/irritation Causes skin irritation.		

- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation No sensitising effects known.

(Contd. on page 8)

Printing date 16.06.2022 Version number 76 (replaces version 75) Revision: 30.03.2022

Trade name: SPRING PRO FLORIST SPRAY ADHESIVE 400 ML

(Contd. of page 7)

- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards

· Endocrine d	lisrupting properties		
<i>78-93-3</i>	butanone	List II	
26523-78-4	tris(nonylphenyl) phosphite	List I	

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxi	· Aquatic toxicity:		
67-64-1 acei	tone		
LC50/96h	8300 mg/l (fish)		
EC50/96h	7200 mg/l (algae)		
LC50 / 48 h	8450 mg/l (crustacean (water flea))		
Hydrocarbo	ns, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
EC50 / 48 h	3 mg/l (daphnia magna)		
EC50 / 72 h	30-100 mg/l (algae)		
LC50/96 h	11.4 mg/l (fish)		
115-10-6 dir	115-10-6 dimethyl ether		
EC50 / 96 h	155 mg/l (algae)		
LC50 / 48 h	>4000 mg/l (daphnia magna)		
LC50 / 96 h	>4000 mg/l (fish)		
109-66-0 pe	ntane		
EC50 / 48 h	9.7 mg/l (daphnia magna)		
EC50 / 96 h	4.26 mg/l (fish)		
LC50 / 96 h	4.26 mg/l (fish)		
78-93-3 bute	none		
LC50 / 48 h	308 mg/l (daphnia magna)		
LC50 / 72 h	1972 mg/l (Pseudokirchneriella Subcapitata)		

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects

LC50 / 96 h 2990 mg/l (fish)

- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

GB

Printing date 16.06.2022 Version number 76 (replaces version 75) Revision: 30.03.2022

Trade name: SPRING PRO FLORIST SPRAY ADHESIVE 400 ML

(Contd. of page 8)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

1/1 7777 1 775 1	
14.1 UN number or ID number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
Class	2.1 Gases.
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler cod	
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1
	litre: Category A. For AEROSOLS with a capacity ab
	1 litre: Category B. For WASTE AEROSOLS: Catego C, Clear of living quarters.

(Contd. on page 10)

Printing date 16.06.2022 Version number 76 (replaces version 75) Revision: 30.03.2022

Trade name: SPRING PRO FLORIST SPRAY ADHESIVE 400 ML

	(Contd. of page
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1
	litre:
	Segregation as for class 9. Stow "separated from" class except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class.
14.7 Maritime transport in bulk accord	ding to IMO
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E0
• • • • • • • • • • • • • • • • • • • •	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H224 Extremely flammable liquid and vapour.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

(Contd. on page 11)

Printing date 16.06.2022 Version number 76 (replaces version 75) Revision: 30.03.2022

Trade name: SPRING PRO FLORIST SPRAY ADHESIVE 400 ML

(Contd. of page 10)

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Department issuing SDS: R&D legislation and regulatory advisor
- · Contact: e-mail: sds-nl@european-aerosols.com
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 1: Flammable liquids – Category 1

Flam. Liq. 2: Flammable liquids - Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* * Data compared to the previous version altered.

GB