

Diese Datei enthält die Sicherheitsdatenblätter zu allen Farbtönen, Sets und Displays der KREUL Magic Marble Marmorierfarbe. Sie enthält Bestandteile mit unterschiedlicher Kennzeichnung. Die Erstellung eines gemeinsamen Sicherheitsdatenblattes ist daher nicht möglich. Deshalb finden sich im Anhang die Sicherheitsdatenblätter zu den einzelnen Bestandteilen.

This file contains the safety data sheets for all colors, sets and displays for KREUL Magic Marble Marbling paint. It contains components with different labels. It is therefore not possible to create a unique safety data sheet. The safety data sheets for the individual components can be found in the appendix.

Folgende Sets und Displays sind enthalten / Following sets and displays are included:

Artikelnummer / Article number **73600**
Handelsname / Trade name KREUL Magic Marble Marmorierfarben Set Grundfarben 6 x 20 ml
KREUL Magic Marble Marbling paint Basic colors 20 ml Set of 6

Bestandteile / Components:

KREUL Magic Marble Marmorierfarbe Weiß 20 ml / KREUL Magic Marble Marbling paint White 20 ml
KREUL Magic Marble Marmorierfarbe Sonnengelb 20 ml / KREUL Magic Marble Marbling paint Sun Yellow 20 ml
KREUL Magic Marble Marmorierfarbe Rot 20 ml / KREUL Magic Marble Marbling paint Red 20 ml
KREUL Magic Marble Marmorierfarbe Blau 20 ml / KREUL Magic Marble Marbling paint Blue 20 ml
KREUL Magic Marble Marmorierfarbe Grün 20 ml / KREUL Magic Marble Marbling paint Green 20 ml
KREUL Magic Marble Marmorierfarbe Schwarz 20 ml / KREUL Magic Marble Marbling paint Black 20 ml

Artikelnummer / Article number **73610**
Handelsname / Trade name KREUL Magic Marble Marmorierfarben Set Metallic 6 x 20 ml
KREUL Magic Marble Marbling paint Metallic colors 20 ml Set of 6

Bestandteile / Components:

KREUL Magic Marble Marmorierfarbe Silber 20 ml / KREUL Magic Marble Marbling paint Silver 20 ml
KREUL Magic Marble Marmorierfarbe Gold 20 ml / KREUL Magic Marble Marbling paint Gold 20 ml
KREUL Magic Marble Marmorierfarbe Metallic-Rot 20 ml / KREUL Magic Marble Marbling paint Metallic-Red 20 ml
KREUL Magic Marble Marmorierfarbe Metallic-Violett 20 ml / KREUL Magic Marble Marbling paint Metallic-Violet 20 ml
KREUL Magic Marble Marmorierfarbe Metallic-Blau 20 ml / KREUL Magic Marble Marbling paint Metallic-Blue 20 ml
KREUL Magic Marble Marmorierfarbe Metallic-Grün 20 ml / KREUL Magic Marble Marbling paint Metallic-Green 20 ml

Artikelnummer / Article number **73613**
Handelsname / Trade name KREUL Magic Marble Marmorierfarben Set Chalky Living 6 x 20 ml
KREUL Magic Marble Marbling paint Chalky Living 20 ml Set of 6

Bestandteile / Components:

KREUL Magic Marble Marmorierfarbe Farblos 20 ml / KREUL Magic Marble Marbling paint Colorless 20 ml
KREUL Magic Marble Marmorierfarbe Schwarz 20 ml / KREUL Magic Marble Marbling paint Black 20 ml
KREUL Magic Marble Marmorierfarbe Noble Nougat matt 20 ml / KREUL Magic Marble Marbling paint Noble Nougat matt 20 ml
KREUL Magic Marble Marmorierfarbe Mademoiselle Rosé matt 20 ml / KREUL Magic Marble Marbling paint Mademoiselle Rosé matt 20 ml
KREUL Magic Marble Marmorierfarbe Sir Petrol matt 20 ml / KREUL Magic Marble Marbling paint Sir Petrol matt 20 ml
KREUL Magic Marble Marmorierfarbe Volcanic Gray matt 20 ml / KREUL Magic Marble Marbling paint Volcanic Gray matt 20 ml

Artikelnummer / Article number **73614**
Handelsname / Trade name KREUL Magic Marble Marmorierfarben Set Love Neon! 6 x 20 ml
KREUL Magic Marble Marbling paint Love Neon! 20 ml Set of 6

Bestandteile / Components:

KREUL Magic Marble Marmorierfarbe Weiß 20 ml / KREUL Magic Marble Marbling paint White 20 ml
KREUL Magic Marble Marmorierfarbe Mademoiselle Rosé matt 20 ml / KREUL Magic Marble Marbling paint Mademoiselle Rosé matt 20 ml
KREUL Magic Marble Marmorierfarbe Neongelb 20 ml / KREUL Magic Marble Marbling paint Neon Yellow 20 ml
KREUL Magic Marble Marmorierfarbe Volcanic Gray matt 20 ml / KREUL Magic Marble Marbling paint Volcanic Gray matt 20 ml
KREUL Magic Marble Marmorierfarbe Neonorange 20 ml / KREUL Magic Marble Marbling paint Neon Orange 20 ml
KREUL Magic Marble Marmorierfarbe Neopink 20 ml / KREUL Magic Marble Marbling paint Neon Pink 20 ml

Artikelnummer / Article number **732091**
Handelsname / Trade name KREUL Magic Marble Marmorierfarben Thekendisplay
KREUL Magic Marble Marbling paint counter sales display

Bestandteile / Components:

KREUL Magic Marble Marmorierfarbe Sonnengelb 20 ml / KREUL Magic Marble Marbling paint Sun Yellow 20 ml

KREUL Magic Marble Marmorierfarbe Orange 20 ml / KREUL Magic Marble Marbling paint Orange 20 ml
KREUL Magic Marble Marmorierfarbe Rot 20 ml / KREUL Magic Marble Marbling paint Red 20 ml
KREUL Magic Marble Marmorierfarbe Magenta 20 ml / KREUL Magic Marble Marbling paint Magenta 20 ml
KREUL Magic Marble Marmorierfarbe Violett 20 ml / KREUL Magic Marble Marbling paint Violet 20 ml
KREUL Magic Marble Marmorierfarbe Blau 20 ml / KREUL Magic Marble Marbling paint Blue 20 ml
KREUL Magic Marble Marmorierfarbe Hellgrün 20 ml / KREUL Magic Marble Marbling paint Light Green 20 ml
KREUL Magic Marble Marmorierfarbe Grün 20 ml / KREUL Magic Marble Marbling paint Green 20 ml
KREUL Magic Marble Marmorierfarbe Neonpink 20 ml / KREUL Magic Marble Marbling paint Neon Pink 20 ml
KREUL Magic Marble Marmorierfarbe Silber 20 ml / KREUL Magic Marble Marbling paint Silver 20 ml
KREUL Magic Marble Marmorierfarbe Gold 20 ml / KREUL Magic Marble Marbling paint Gold 20 ml
KREUL Magic Marble Marmorierfarbe Kupfer 20 ml / KREUL Magic Marble Marbling paint Copper 20 ml
KREUL Magic Marble Marmorierfarbe Glitzer-Silber 20 ml / KREUL Magic Marble Marbling paint Glitter-Silver 20 ml
KREUL Magic Marble Marmorierfarbe Glitzer-Gold 20 ml / KREUL Magic Marble Marbling paint Glitter-Gold 20 ml
KREUL Magic Marble Marmorierfarbe Mademoiselle Rosé matt 20 ml / KREUL Magic Marble Marbling paint Mademoiselle Rosé matt 20 ml
KREUL Magic Marble Marmorierfarbe Sir Petrol matt 20 ml / KREUL Magic Marble Marbling paint Sir Petrol matt 20 ml
KREUL Magic Marble Marmorierfarbe Noble Nougat matt 20 ml / KREUL Magic Marble Marbling paint Noble Nougat matt 20 ml
KREUL Magic Marble Marmorierfarbe Volcanic Gray matt 20 ml / KREUL Magic Marble Marbling paint Volcanic Gray matt 20 ml

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.08.2022

Version number 3.2 (replaces version 3.1)

Revision: 24.08.2022

1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** KREUL Magic Marble Marbling paint White, Rose, Light Blue, Silver, Gold, Metallic-Yellow, Metallic-Red, Metallic-Rose, Metallic-Violet, Metallic-Blue, Metallic-Green, Neon Pink, Mademoiselle Rosé matt, Sir Petrol matt, Noble Nougat matt, Volcanic Gray matt 20 ml
- **Article number:**
73201, 73206, 73210, 73219, 73220, 73225, 73226, 73227, 73228, 73229, 73230, 73233, 73234, 73235, 73236, 73237
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Paint
For artists and hobby user.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
C. KREUL GmbH & Co. KG
Carl-Kreul-Straße 2
D-91352 HALLERNDORF
DEUTSCHLAND
Tel. + 49 (0)9545 / 925 - 0
Fax + 49 (0)9545 / 925 - 511
E-Mail: info@c-kreul.de
- **Further information obtainable from:**
Product Safety Department:
Treiber, b.treiber@c-kreul.de
- **1.4 Emergency telephone number:** +44 (0)171 635 91 91

2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02

GHS07

- **Signal word** Warning
- **Hazard-determining components of labelling:**
1-methoxy-2-propanol
Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics
2-methoxy-1-methylethyl acetate
- **Hazard statements**
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.08.2022

Version number 3.2 (replaces version 3.1)

Revision: 24.08.2022

(Contd. of page 1)

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH208 Contains cobalt(II) 2-ethylhexanoate. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Vapours may form explosive mixtures with air. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/ electrical equipment). Take precautionary measures against static discharges.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3	1-methoxy-2-propanol ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	25-<50%
CAS: 64742-48-9 EC number: 919-857-5 Reg.nr.: 01-2119463258-33-XXXX	Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336	10-<20%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39-XXXX	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclenes, <2% aromatics ⚠ Asp. Tox. 1, H304	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	5-<10%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17-XXXX	titanium dioxide ⚠ Carc. 2, H351	1-<2.5%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29-XXXX	cobalt(II) 2-ethylhexanoate ⚠ Repr. 1A, H360Fd; ⚠ Aquatic Acute 1, H400; ⚠ Eye Irrit. 2, H319; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	<0.03%

Additional information:

Benzene (EINECS 200-753-7) <0.1%. (Note P Annex VI to Directive (EC) No 1272/2008)

For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Wash with water and acidic soap.

If skin irritation continues, consult a doctor.

After eye contact:

Remove contact lenses.

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Seek immediate medical advice.

Rinse out mouth and then drink plenty of water.

Administer medicinal carbon.

A person vomiting while laying on their back should be turned onto their side.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

5 Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment: Wear self-contained respiratory protective device.

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.08.2022

Version number 3.2 (replaces version 3.1)

Revision: 24.08.2022

(Contd. of page 2)

· **Additional information** Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 - Ensure adequate ventilation
 - Use respiratory protective device against the effects of fumes/dust/aerosol.
 - Keep away from ignition sources.
 - Wear protective equipment. Keep unprotected persons away.
 - Mount respiratory protective device.
- **6.2 Environmental precautions:**
 - Keep contaminated washing water and dispose of appropriately.
 - In case of seepage into the ground inform responsible authorities.
 - Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Dispose contaminated material as waste according to item 13.
 - Ensure adequate ventilation.
- **6.4 Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

7 Handling and storage

- **7.1 Precautions for safe handling**
 - Take note of emission threshold.
 - Prevent formation of aerosols.
 - Ensure good ventilation/exhaustion at the workplace.
 - Keep away from heat and direct sunlight.
- **Information about fire - and explosion protection:**
 - Fumes can combine with air to form an explosive mixture.
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:** Store in a cool location.
 - **Information about storage in one common storage facility:**
 - Do not store together with alkalis (caustic solutions).
 - Do not store together with oxidising and acidic materials.
 - **Further information about storage conditions:**
 - Store receptacle in a well ventilated area.
 - Keep container tightly sealed.
 - Store in a cool place.
 - Protect from heat and direct sunlight.
 - Protect from frost.
 - **Storage class:** 3
- **7.3 Specific end use(s)** See chapter 1.2.

8 Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

WEL	Short-term value: 560 mg/m ³ , 150 ppm
	Long-term value: 375 mg/m ³ , 100 ppm
Sk	

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
Sk	

13463-67-7 titanium dioxide

WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
Sk	

136-52-7 cobalt(II) 2-ethylhexanoate

WEL	Long-term value: 0.1 mg/m ³
	as Co; Carc, Sen

· DNELs

107-98-2 1-methoxy-2-propanol

Oral	long-term exposure-systemic effects	33 mg/kg (general population)
------	-------------------------------------	-------------------------------

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.08.2022

Version number 3.2 (replaces version 3.1)

Revision: 24.08.2022

(Contd. of page 3)

Dermal	long-term exposure-systemic effects	183 mg/kg bw/d (general population) 78 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	43.9 mg/m ³ (general population) 369 mg/m ³ (worker)
64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics		
Oral	long-term exposure-systemic effects	300 mg/kg (general population)
Dermal	long-term exposure-systemic effects	300 mg/kg bw/d (general population) 300 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	900 mg/m ³ (general population) 1,500 mg/m ³ (worker)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	long-term exposure-systemic effects	1.67 mg/kg (general population)
Dermal	long-term exposure-systemic effects	54.8 mg/kg bw/d (general population) 153.5 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	33 mg/m ³ (general population) 275 mg/m ³ (worker)

· **PNECs****107-98-2 1-methoxy-2-propanol**

water	100 mg/l
freshwater	10 mg/l
marine water	1 mg/l
sewage treatment plant (STP)	100 mg/l
freshwater sediment	52.3 mg/kg
marine sediment	5.2 mg/kg
soil	4.59 mg/kg

108-65-6 2-methoxy-1-methylethyl acetate

water	6.35 mg/l
freshwater	0.635 mg/l
marine water	0.0635 mg/l
sewage treatment plant (STP)	100 mg/l
freshwater sediment	3.29 mg/kg
marine sediment	0.329 mg/kg
soil	0.29 mg/kg

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Appropriate engineering controls** No further data; see item 7.· **Individual protection measures, such as personal protective equipment**· **General protective and hygienic measures:**

Do not eat, drink, smoke or sniff while working.

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Use suitable respiratory protective device when high concentrations are present.· **Hand protection**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.38 mmValue for the permeation: Level ≤ 4 h· **As protection from splashes gloves made of the following materials are suitable:**

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.3 mmValue for the permeation: Level $\leq 10 - 30$ min

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.08.2022

Version number 3.2 (replaces version 3.1)

Revision: 24.08.2022

(Contd. of page 4)

· **Eye/face protection**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	Undetermined.
· Flammability	Flammable.
· Lower and upper explosion limit	
· Lower:	0.6 Vol %
· Upper:	13.8 Vol %
· Flash point:	25 °C
· Ignition temperature:	>200 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity at 40 °C	>20.5 mm ² /s
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	0.954–0.995 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· **9.2 Other information**

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	60.3–<61.2 %
· Change in condition	
· Evaporation rate	Not determined.

· **Information with regard to physical hazard classes**

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

10 Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.08.2022

Version number 3.2 (replaces version 3.1)

Revision: 24.08.2022

(Contd. of page 5)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Keep away from oxidizing agents, strong alkaline and acidic materials.
- **10.6 Hazardous decomposition products:**
In case of fire, the following can be released:
Carbon monoxide and carbon dioxide

11 Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

107-98-2 1-methoxy-2-propanol

Oral	LD50	4,016 mg/kg (rat) (EU B.1, ECHA)
Dermal	LD50	13,000 mg/kg (rab)
Inhalative	LC50/4h	>2,000 mg/kg (rat) (EU B.3, ECHA) 30.04 mg/m ³ (rat) (ECHA)

64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rab)
Inhalative	LC50/4h	>4,951 mg/m ³ (rat)

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclenes, <2% aromatics

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rab)
Inhalative	LC50/4h	>4,951 mg/m ³ (rat)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rab)
Inhalative	LC50/4h	>2,000 mg/kg (rat) (OECD 401) >10,000 mg/l (rat)

13463-67-7 titanium dioxide

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4h	>6.82 mg/m ³ (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

12 Ecological information

12.1 Toxicity

Aquatic toxicity:

107-98-2 1-methoxy-2-propanol

LC50/96h	1,000 mg/l (oncorhynchus mykiss) (OECD 203)
LC50/48h	21,100–25,900 mg/l (daphnia magna) (ESR-ES-15)
ErC50	>1,000 mg/l /7d (pseudokirchneriella subcapitata) (ECHA)

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclenes, <2% aromatics

LC50/48h	>1,000 mg/l (oncorhynchus mykiss)
EC50/48h	>1,000 mg/l (daphnia magna)
EC50/72h	>1,000 mg/l (pseudokirchneriella subcapitata)
EL50/48h	>1,000 mg/l (daphnia magna)
LL50/48h	>1,000 mg/l (daphnia magna)

108-65-6 2-methoxy-1-methylethyl acetate

LC50/96h	180 mg/l (oncorhynchus mykiss)
----------	--------------------------------

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.08.2022

Version number 3.2 (replaces version 3.1)

Revision: 24.08.2022

(Contd. of page 6)

EC50/48h	>500 mg/l (daphnia magna)
(EbCx) 10%	>1,000 mg/l (microorganisms)
EC50/21d	>100 mg/l (daphnia magna) (OECD 211)
ErC50/96h	>1,000 mg/l (pseudokirchneriella subcapitata)
LC50	63.5 mg/l (oryzias latipes) (OECD 204)
LOEC/96h	>1,000 mg/l (pseudokirchneriella subcapitata)
NOEC/48d	47.5 mg/l (oryzias latipes) (OECD 204)

13463-67-7 titanium dioxide

EC50	>100 mg/l (pseudokirchneriella subcapitata) (OECD 201)
	>10,000 mg/l (skeletonema costatum) (ISO 10253)
NOEC	>100,000 mg/l (hyalella azteca) (ASTM 1706)
LC50	>10,000 mg/l (acartia tonsa) (ISO 14669 (1999) ISO 5667-16 (1998))
	>1,000 mg/l (daphnia magna) (OECD 202)
	>1,000 mg/l (pimephales promelas) (EPA-540/9-85-006)

136-52-7 cobalt(II) 2-ethylhexanoate

EC50/72h	0.528 mg/l (algae)
----------	--------------------

12.2 Persistence and degradability**Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclenes, <2% aromatics**

Oxygen consumption	80 % /28d (OECD 301 F)
--------------------	------------------------

108-65-6 2-methoxy-1-methylethyl acetate

Carbon dioxide production	90 % /28d (OECD 301 F)
DOC removal	99 % /28d (OECD 301 F)
Oxygen consumption	83 % /28d (OECD 301 F)

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Dispose of packaging according to regulations on the disposal of packagings.

14 Transport information

- | | |
|---|-----------------------------|
| · 14.1 UN number or ID number | UN1263 |
| · ADR, IMDG, IATA | |
| · 14.2 UN proper shipping name | 1263 PAINT |
| · ADR | PAINT |
| · IMDG, IATA | |
| · 14.3 Transport hazard class(es) | |
| · ADR, IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids. |
| · Label | 3 |
| · 14.4 Packing group | III |
| · ADR, IMDG, IATA | |
| · 14.5 Environmental hazards: | Not applicable. |
| · 14.6 Special precautions for user | Warning: Flammable liquids. |
| · Hazard identification number (Kemler code): | 30 |
| · EMS Number: | F-E,S-E |

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.08.2022

Version number 3.2 (replaces version 3.1)

Revision: 24.08.2022

(Contd. of page 7)

· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c** FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H360Fd May damage fertility. Suspected of damaging the unborn child.
- H400 Very toxic to aquatic life.
- H412 Harmful to aquatic life with long lasting effects.

· **Department issuing SDS:** Product Safety Department

· **Contact:** B. Treiber, b.treiber@c-kreul.de

· **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (UK REACH)
- PNEC: Predicted No-Effect Concentration (UK REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids – Category 3
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1A: Skin sensitisation – Category 1A
- Carc. 2: Carcinogenicity – Category 2
- Repr. 1A: Reproductive toxicity – Category 1A
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.09.2022

Version number 3.2 (replaces version 3.1)

Revision: 15.09.2022

1 Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** KREUL Magic Marble Marbling paint Lemon, Sun Yellow, Orange, Red, Zinia, Magenta, Violet, Blue, Dark Blue, Turquoise, Light Green, Green, Ocher, Brown, Black, Copper, Colorless, Glitter-Silver, Glitter-Gold, Neon Yellow, Neon Orange 20 ml

· **Article number:**

73202, 73203, 73204, 73205, 73207, 73208, 73209, 73211, 73212, 73213, 73214, 73215, 73216, 73217, 73218, 73221, 73222, 73223, 73224, 73231, 73232

· **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.

· **Application of the substance / the mixture**

Paint
For artists and hobby user.

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**
C. KREUL GmbH & Co. KG
Carl-Kreul-Straße 2
D-91352 HALLERNDORF
DEUTSCHLAND
Tel. + 49 (0)9545 / 925 - 0
Fax + 49 (0)9545 / 925 - 511
E-Mail: info@c-kreul.de

· **Further information obtainable from:**

Product Safety Department:
Treiber, b.treiber@c-kreul.de

· **1.4 Emergency telephone number:** +44 (0)171 635 91 91

2 Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Warning

· **Hazard-determining components of labelling:**

1-methoxy-2-propanol
Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics
2-methoxy-1-methylethyl acetate

· **Hazard statements**

H226 Flammable liquid and vapour.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.09.2022

Version number 3.2 (replaces version 3.1)

Revision: 15.09.2022

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P271 Use only outdoors or in a well-ventilated area.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH208 Contains cobalt(II) 2-ethylhexanoate. May produce an allergic reaction.

2.3 Other hazards

Vapours may form explosive mixtures with air. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/ electrical equipment). Take precautionary measures against static discharges.

Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

3.2 Mixtures

- **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3	1-methoxy-2-propanol ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	25-<50%
CAS: 64742-48-9 EC number: 919-857-5 Reg.nr.: 01-2119463258-33-XXXX	Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336	10-<20%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39-XXXX	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclenes, <2% aromatics ⚠ Asp. Tox. 1, H304	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	5-<10%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29-XXXX	cobalt(II) 2-ethylhexanoate ⚠ Repr. 1A, H360Fd; ⚠ Aquatic Acute 1, H400; ⚠ Eye Irrit. 2, H319; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	<0.04%

Additional information:

Benzene (EINECS 200-753-7) <0.1%. (Note P Annex VI to Directive (EC) No 1272/2008)

For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

4.1 Description of first aid measures

- **General information:** Immediately remove any clothing soiled by the product.

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

After skin contact:

Wash with water and acidic soap.
If skin irritation continues, consult a doctor.

After eye contact:

Remove contact lenses.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Seek immediate medical advice.
Rinse out mouth and then drink plenty of water.
Administer medicinal carbon.

A person vomiting while laying on their back should be turned onto their side.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed or in case of vomiting, danger of entering the lungs.

5 Firefighting measures

5.1 Extinguishing media

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.09.2022

Version number 3.2 (replaces version 3.1)

Revision: 15.09.2022

(Contd. of page 2)

- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information** Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Use respiratory protective device against the effects of fumes/dust/aerosol.
Keep away from ignition sources.
Wear protective equipment. Keep unprotected persons away.
Mount respiratory protective device.
- **6.2 Environmental precautions:**
Keep contaminated washing water and dispose of appropriately.
In case of seepage into the ground inform responsible authorities.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **7.1 Precautions for safe handling**
Take note of emission threshold.
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Fumes can combine with air to form an explosive mixture.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:**
Do not store together with oxidising and acidic materials.
Do not store together with alkalis (caustic solutions).
- **Further information about storage conditions:**
Store receptacle in a well ventilated area.
Keep container tightly sealed.
Store in a cool place.
Protect from frost.
Protect from heat and direct sunlight.
- **Storage class:** 3
- **7.3 Specific end use(s)** See chapter 1.2.

8 Exposure controls/personal protection

8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

107-98-2 1-methoxy-2-propanol	
WEL	Short-term value: 560 mg/m ³ , 150 ppm
	Long-term value: 375 mg/m ³ , 100 ppm
Sk	
108-65-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
Sk	

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.09.2022

Version number 3.2 (replaces version 3.1)

Revision: 15.09.2022

(Contd. of page 3)

136-52-7 cobalt(II) 2-ethylhexanoate		
WEL	Long-term value: 0.1 mg/m ³ as Co; Carc, Sen	
DNELs		
107-98-2 1-methoxy-2-propanol		
Oral	long-term exposure-systemic effects	33 mg/kg (general population)
Dermal	long-term exposure-systemic effects	183 mg/kg bw/d (general population) 78 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	43.9 mg/m ³ (general population) 369 mg/m ³ (worker)
64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics		
Oral	long-term exposure-systemic effects	300 mg/kg (general population)
Dermal	long-term exposure-systemic effects	300 mg/kg bw/d (general population) 300 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	900 mg/m ³ (general population) 1,500 mg/m ³ (worker)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	long-term exposure-systemic effects	1.67 mg/kg (general population)
Dermal	long-term exposure-systemic effects	54.8 mg/kg bw/d (general population) 153.5 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	33 mg/m ³ (general population) 275 mg/m ³ (worker)
PNECs		
107-98-2 1-methoxy-2-propanol		
water	100 mg/l	
freshwater	10 mg/l	
marine water	1 mg/l	
sewage treatment plant (STP)	100 mg/l	
freshwater sediment	52.3 mg/kg	
marine sediment	5.2 mg/kg	
soil	4.59 mg/kg	
108-65-6 2-methoxy-1-methylethyl acetate		
water	6.35 mg/l	
freshwater	0.635 mg/l	
marine water	0.0635 mg/l	
sewage treatment plant (STP)	100 mg/l	
freshwater sediment	3.29 mg/kg	
marine sediment	0.329 mg/kg	
soil	0.29 mg/kg	

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Do not eat, drink, smoke or sniff while working.

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Use suitable respiratory protective device when high concentrations are present.

· **Hand protection**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.38 mm

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.09.2022

Version number 3.2 (replaces version 3.1)

Revision: 15.09.2022

(Contd. of page 4)

Value for the permeation: Level \leq 4 h· **As protection from splashes gloves made of the following materials are suitable:**

Butyl rubber, BR

Recommended thickness of the material: \geq 0.3 mmValue for the permeation: Level \leq 10 - 30 min· **Eye/face protection**

Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Fluid

Colour:

According to product specification

Odour:

Characteristic

Odour threshold:

Not determined.

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

Undetermined.

Flammability

Not applicable.

Lower and upper explosion limit

Lower:

0.6 Vol %

Upper:

13.8 Vol %

Flash point:

25 °C

Ignition temperature:

>200 °C

Decomposition temperature:

Not determined.

pH

Not determined.

Viscosity:

Kinematic viscosity at 40 °C

>20.5 mm²/s

Dynamic:

Not determined.

Solubility

water:

Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)

Not determined.

Vapour pressure:

Not determined.

Density and/or relative density

Density at 20 °C:

0.902–0.972 g/cm³

Relative density

Not determined.

Vapour density

Not determined.

9.2 Other information

Appearance:

Form:

Fluid

Important information on protection of health and environment, and on safety.

Auto-ignition temperature:

Product is not selfigniting.

Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Solvent content:

Organic solvents:

60-80 %

Change in condition

Evaporation rate

Not determined.

Information with regard to physical hazard classes

Explosives

Void

Flammable gases

Void

Aerosols

Void

Oxidising gases

Void

Gases under pressure

Void

Flammable liquids

Flammable liquid and vapour.

Flammable solids

Void

Self-reactive substances and mixtures

Void

Pyrophoric liquids

Void

Pyrophoric solids

Void

Self-heating substances and mixtures

Void

Substances and mixtures, which emit flammable gases in contact with water

Void

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.09.2022

Version number 3.2 (replaces version 3.1)

Revision: 15.09.2022

(Contd. of page 5)

· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

10 Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Keep away from oxidizing agents, strong alkaline and acidic materials.
- **10.6 Hazardous decomposition products:**
In case of fire, the following can be released:
Carbon monoxide and carbon dioxide

11 Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

107-98-2 1-methoxy-2-propanol		
Oral	LD50	4,016 mg/kg (rat) (EU B.1, ECHA)
Dermal	LD50	13,000 mg/kg (rab) >2,000 mg/kg (rat) (EU B.3, ECHA)
Inhalative	LC50/4h	30.04 mg/m ³ (rat) (ECHA)
64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rab)
Inhalative	LC50/4h	>4,951 mg/m ³ (rat)
Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclenes, <2% aromatics		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rab)
Inhalative	LC50/4h	>4,951 mg/m ³ (rat)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8,532 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rab) >2,000 mg/kg (rat) (OECD 401)
Inhalative	LC50/4h	>10,000 mg/l (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

12 Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

107-98-2 1-methoxy-2-propanol	
LC50/96h	1,000 mg/l (oncorhynchus mykiss) (OECD 203)
LC50/48h	21,100–25,900 mg/l (daphnia magna) (ESR-ES-15)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.09.2022

Version number 3.2 (replaces version 3.1)

Revision: 15.09.2022

(Contd. of page 6)

ErC50	>1,000 mg/l /7d (pseudokirchneriella subcapitata) (ECHA)
Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclenes, <2% aromatics	
LC50/48h	>1,000 mg/l (oncorhynchus mykiss)
EC50/48h	>1,000 mg/l (daphnia magna)
EC50/72h	>1,000 mg/l (pseudokirchneriella subcapitata)
EL50/48h	>1,000 mg/l (daphnia magna)
LL50/48h	>1,000 mg/l (daphnia magna)
108-65-6 2-methoxy-1-methylethyl acetate	
LC50/96h	180 mg/l (oncorhynchus mykiss)
EC50/48h	>500 mg/l (daphnia magna)
(EbCx) 10%	>1,000 mg/l (microorganisms)
EC50/21d	>100 mg/l (daphnia magna) (OECD 211)
ErC50/96h	>1,000 mg/l (pseudokirchneriella subcapitata)
LC50	63.5 mg/l (oryzias latipes) (OECD 204)
LOEC/96h	>1,000 mg/l (pseudokirchneriella subcapitata)
NOEC/48d	47.5 mg/l (oryzias latipes) (OECD 204)
136-52-7 cobalt(II) 2-ethylhexanoate	
EC50/72h	0.528 mg/l (algae)
12.2 Persistence and degradability	
Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclenes, <2% aromatics	
Oxygen consumption	80 % /28d (OECD 301 F)
108-65-6 2-methoxy-1-methylethyl acetate	
Carbon dioxide production	90 % /28d (OECD 301 F)
DOC removal	99 % /28d (OECD 301 F)
Oxygen consumption	83 % /28d (OECD 301 F)

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**
- Disposal must be made according to official regulations.
- Dispose of packaging according to regulations on the disposal of packagings.

14 Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1263
- **14.2 UN proper shipping name**
- **ADR** 1263 PAINT
- **IMDG, IATA** PAINT

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.09.2022

Version number 3.2 (replaces version 3.1)

Revision: 15.09.2022

(Contd. of page 7)

14.3 Transport hazard class(es)

· ADR, IMDG, IATA



· Class 3 Flammable liquids.
· Label 3

14.4 Packing group

· ADR, IMDG, IATA III

· 14.5 Environmental hazards: Not applicable.

· 14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code): 30

· EMS Number: F-E,S-E

· Stowage Category A

· 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· Transport category 3
· Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1263 PAINT, 3, III

15 Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H360Fd May damage fertility. Suspected of damaging the unborn child.
- H400 Very toxic to aquatic life.
- H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: Product Safety Department

· Contact: B. Treiber, b.treiber@c-kreul.de

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.09.2022

Version number 3.2 (replaces version 3.1)

Revision: 15.09.2022

(Contd. of page 8)

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1A: Skin sensitisation – Category 1A
Repr. 1A: Reproductive toxicity – Category 1A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**

GB