

ASTRALPOOL – LIQUID FILNET



Cleans the inside of the sand filters

- Removes limescale and dirt deposited inside sand filters
- Quick water rinse

LIQUID	EFFICACY	POOLS WITH SAND FILTERS	DOSAGE
			2L of water 2L of product / 10Kg

PROPERTIES

Appearance	Liquid
Colour	Yellow
Density	1,13 - 1,17 g/cm. ³
pH in supply	0

CHARACTERISTICS

Liquid acidic product for elimination of encrustations produced by water salts and dirt deposits formed inside sand filters.

It does not give off either damaging smoke nor steam.

This liquid product is suitable for cleaning of stainless steel or polyester filters.

Non foaming. Produces effervescence as the lime dissolves.

It can be easily applied and rinsed by running water.

INSTRUCTIONS FOR USE

This treatment is valid only for filters with silex or sand filtering charge.

With the filter at standstill and uncovered, drain all the water from inside the filter through the bottom valve. Shut the drain valve and pour 2L of water through the filter mouth, followed by 2L of product FILNET per 10kg of sand or silex, approximately.

This added solution must cover the level of the sand by 20 to 30 cm.

Leave the product to react with the lime and dirtiness present in the filter. When the effervescence (bubbles) ceases after a prudential time has elapsed (some 4 to 8 hours), shut the filter cover, move the valve cock to washing position and pass water through the filter to rinse it out.

DOSAGE

Pour 2 liters of water through the filter mouth, followed by 2 liters of product FILNET for every 10 Kg of sand or silex approximately.

These doses are the ones suggested and can be modified according to the own characteristics of every swimming pool, climate, etc.