



ASTRALPOOL – CHLORINE LENT 250g



Trichloro treatment for disinfecting the pool

- Continuous, slow dissolving disinfection
- Stable chloro, greater duration on water
- Highly concentrated

TABLET	DURATION	ALL TYPES OF POOLS	DOSAGE
 250G	 Weekly		1 TABLET PER 25m³

PROPERTIES

Appearance	Solid in tablets (250g)
Colour	White
pH (1%)	2 - 3

CHARACTERISTICS

Solid component with a slow dissolution, highly stabilised, for the disinfection and maintenance of crystalline and hygienically pure water.

Product adequate for the swimming pool disinfection built with ceramic materials. This product can neither be in direct contact with the swimming pools bade with liner, polyester or vinyl, nor with painted swimming pools because it may cause discolorations.

INSTRUCTIONS FOR USE

Always adjust the pH before adding chlorine to the water, to make it as effective as possible.

Introduce the necessary product doses inside the skimmers. Connect the filtering equipment after and you will have the product dissolved in the water, because water will be flowing through the skimmers.

It is necessary that all the water in the swimming pool flow again through the purifier equipment.

The residual free chlorine will have to be placed between 0,5 and 2 mg/l. This value will easily be measured using an analyzer chlorine and pH case. This control will have to be done twice a day minimum.

DOSAGE

Initial treatment: Add 15 grs. of ASTRALPOOL – 200GR Chlorine Shock for m³ of water. Wait for two hours before adjusting the pH level between 7,2 - 7,6 using either ASTRALPOOL - 10 pH Minus solid or ASTRALPOOL - 20 pH Plus solid.

The initial treatment will have to be repeated whenever you notice a lack of transparency in the water.

Maintenance treatment: Once we have the pH water adjusted, the maintenance treatment can be done in two different ways:

A) Put into the skimmers basket 1 compact of product for every 25 m³ of water. Do this every 10-15 days.

B) In the instalments in which a doser is used, fill it with compacts of product and afterwards, make the water flow through the doser.

These doses are the ones suggested and can be modified according to the own characteristics of every swimming pool, climate, etc.