(in accordance with Regulation (EU) 2020/878)

# ctx235 SLEEPY



Version 1 Date of compilation: 17/01/2022 Page 1 of 13
Print date: 23/06/2022

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: ctx235 SLEEPY

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against.

Desinfectant-algaecide-flocculant

#### Uses advised against:

Uses other than those recommended.

#### 1.3 Details of the supplier of the safety data sheet.

Company: FLUIDRA COMERCIAL ESPAÑA

Address: Av. Alcalde Barnils, 69
City: 08174 Sant Cugat del Vallès

Province: Barcelona (España)
Telephone: telf: 902 42 32 22
Fax: +34 93 713 41 11
E-mail: fds@inquide.com

Web: www.ctxprofessional.com

#### 1.4 Emergency telephone number: (Available 24 hours)

Anti poisoning centre:

ITALY (Rome): 06/305 43 43 ITALY (Milan): 02/66 10 10 29 SPAIN: +34 91 562 04 20

FRANCE (Paris): 01 40 05 48 48 FRANCE (Tolousse): 05 61 77 74 47 FRANCE (Marseille): 04 91 75 25 25

PORTUGAL: 808 250 143

BELGIQUE (Brussel): (+34) 070 245 245

CAV accreditati: Roma +39 06 68 59 3726; Foggia +39 800 18 34 59; Napoli +39 081 54 53 333; Roma +39 06 49 97 80 00; Roma +39 06 30 54 343; Firenze +39 055 79 47 819; Pavia +39 0382 24 444; Milano +39 02 66 10 10 29; Bergamo +39 800 88

33 00; Verona +39 800 01 18 58.

#### **SECTION 2: HAZARDS IDENTIFICATION.**

# 2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008:

Acute Tox. 4 : Harmful if swallowed. Eye Dam. 1 : Causes serious eye damage. STOT SE 3 : May cause respiratory irritation. STOT SE 3 : May cause drowsiness or dizziness. Aquatic Acute 1 : Very toxic to aquatic life.

Aquatic Chronic 1: Very toxic to aquatic life with long lasting effects.

#### 2.2 Label elements.

## Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:

(in accordance with Regulation (EU) 2020/878)

# ctx235 SLEEPY



Page 2 of 13

**Version 1** Date of compilation: 17/01/2022 Print date: 23/06/2022







#### Signal Word:

# **Danger**

#### Hazard statements:

Harmful if swallowed. H302 H318 Causes serious eye damage. H335 May cause respiratory irritation.

H410 Very toxic to aquatic life with long lasting effects.

#### Precautionary statements:

Avoid breathing dust. P261

P271 Use only outdoors or in a well-ventilated area. P270 Do not eat, drink or smoke when using this product. P280 Wear protective gloves/protective clothing/eye protection.

P264 Wash hands thoroughly after handling.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P102 Keep out of reach of children.

P405 Store locked up.

P273 Avoid release to the environment.

P391 Collect spillage.

Dispose of contents/container in accordance with applicable regulations. P501

# **EUH statements:**

EUH031 Contact with acids liberates toxic gas.

EUH206 Warning! Do not use together with other products. May release dangerous gases (chlorine).

Contains: symclosene boric acid

copper sulphate pentahydrate

#### Active substances:

symclosene, 92%;

copper sulphate pentahydrate, 1%;

# 2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

#### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.**

### 3.1 Substances.

Not Applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008
-------------	------	-------------	---

(in accordance with Regulation (EU) 2020/878)

# ctx235 SLEEPY



Version 1 Date of compilation: 17/01/2022 Page 3 of 13
Print date: 23/06/2022

			Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 613-031- 00-5 CAS No: 87-90-1 EC No: 201-782-8	symclosene	80 - 100 %	Acute Tox. 4 *, H302 - Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Eye Irrit. 2, H319 - Ox. Sol. 2, H272 - STOT SE 3, H335	-
Index No: 005-007- 00-2 CAS No: 10043-35-3 EC No: 233-139-2 Registration No: 01- 2119486683-25-XXXX	[5] boric acid	0.1 - 0.3 %	Repr. 1B, H360FD	Repr. 1B, H360FD: C ≥ 5,5 %
CAS No: 10043-01-3 EC No: 233-135-0 Registration No: 01- 2119531538-36-XXXX	Aluminium sulfate	1 - 3 %	Eye Dam. 1, H318	-
Index No: 029-023- 00-4 CAS No: 7758-99-8 EC No: 231-847-6	copper sulphate pentahydrate	0 - 2 %	Acute Tox. 4, H302 - Aquatic Acute 1, H400 (M=10) - Aquatic Chronic 1, H410 - Eye Dam. 1, H318	-

<sup>(\*)</sup> The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

#### **SECTION 4: FIRST AID MEASURES.**

### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### **Inhalation**

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

#### Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

#### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

#### Ingestion

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

<sup>\*</sup> See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

<sup>[2]</sup> Substance with a national workplace exposure limit (see section 8.1).

<sup>[5]</sup> Substance included in the list established under Article 59, paragraph 1, REACH (Candidate substance).

(in accordance with Regulation (EU) 2020/878)

# ctx235 SLEEPY



Version 1 Date of compilation: 17/01/2022 Page 4 of 13
Print date: 23/06/2022

Contact with eyes may cause irreversible damage.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract.

#### **SECTION 5: FIREFIGHTING MEASURES.**

The product is NOT classified as flammable, in case of fire the following measures should be taken:

#### 5.1 Extinguishing media.

#### Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

#### **Unsuitable extinguishing media:**

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

Suitable extinguishing media: CO2 in small fires and water in large quantities (small amounts of water may aggravate the situation)

Unsuitable extinguishing media: Dry powder, Halogenated hydrocarbon, ABC powder.

#### 5.2 Special hazards arising from the substance or mixture.

#### Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES.**

### 6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

#### 6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

#### 6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

#### **SECTION 7: HANDLING AND STORAGE.**

#### 7.1 Precautions for safe handling.

(in accordance with Regulation (EU) 2020/878)

# ctx235 SLEEPY



Version 1 Date of compilation: 17/01/2022 Page 5 of 13
Print date: 23/06/2022

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

		Qualifying quantity (tonnes) for the application of	
Code	Description	Lower-tier requirements	Upper-tier requirements
E1	ENVIRONMENTAL HAZARDS - Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1	100	200
P8	OXIDISING LIQUIDS AND SOLIDS	50	200

#### 7.3 Specific end use(s).

None in particular.

### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.**

#### 8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values. Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
boric acid	DNEL	Inhalation, Chronic, Systemic effects	8,3
CAS No: 10043-35-3 EC No: 233-139-2	(Workers)		(mg/m³)
Aluminium sulfate	DNEL (Workers)	Dermal, Chronic, Local effects	10 (mg/kg)
CAS No: 10043-01-3 EC No: 233-135-0	DNEL (Consumers)	Oral, Chronic, Systemic effects	5 (mg/kg)
EC NO. 255-155-0	DNEL (Workers)	Dermal, Chronic, Systemic effects	1,8 (mg/m3)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
Aluminium sulfate	Water (freshwater)	34,6 (mg/kg)
CAS No: 10043-01-3	Sediment (marine water)	3,46 (mg/kg)
EC No: 233-135-0	Soil	33,1 (mg/kg)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

CAS: 87-90-1

(in accordance with Regulation (EU) 2020/878)

# ctx235 SLEEPY



Version 1 Date of compilation: 17/01/2022 Page 6 of 13
Print date: 23/06/2022

TLV TWA - 0.5 ppm (1.5 mg/m3) Cl gas TLV STEL - 1 ppm (3.0 mg/m3) Cl gas

CAS: 10043-01-3 TLV TWA - 2 mg/m3 (Al) **8.2 Exposure controls.** 

## **Measures of a technical nature:**

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	Desinfectant-algaecide-flocculant		
Breathing protect			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach		
Observations:	the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
Hand protection:			
PPE:	Protective gloves against chemicals.		
Characteristics:	«CE» marking, category III.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight.  Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride) Breakthrough time (min.): Material thickness (mm): 0,35		
Eye protection:			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		
Skin protection:			
PPE:	Chemical protective clothing		
Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.		
CEN standards:	EN 464,EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034		
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.		
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.		
PPE:	Work footwear.		
Characteristics: CEN standards:	«CE» marking, category II. EN ISO 13287, EN 20347		
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.		

(in accordance with Regulation (EU) 2020/878)

# ctx235 SLEEPY



Version 1 Date of compilation: 17/01/2022 Page 7 of 13
Print date: 23/06/2022

Observations: Work footwear for professional use includes protection elements aimed at protecting users against any

injury resulting from an accident

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.**

### 9.1 Information on basic physical and chemical properties.

Physical state: Solid Colour: White anb blue Odour: Similar to bleach

Odour threshold: Not applicable/Not available due to the nature/properties of the product

Melting point: > 230 °C

Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: Not applicable/Not available due to the nature/properties of the product

Flammability: > 250 °C

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product Upper explosion limit: Not applicable/Not available due to the nature/properties of the product

Flash point: Not applicable/Not available due to the nature/properties of the product

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

pH: 2,1 - 3 (1%)

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product

Solubility: Not applicable/Not available due to the nature/properties of the product Hydrosolubility: Not applicable/Not available due to the nature/properties of the product Liposolubility: Not applicable/Not available due to the nature/properties of the product

Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product

Vapour pressure: Not applicable/Not available due to the nature/properties of the product Absolute density: Not applicable/Not available due to the nature/properties of the product Relative density: 1,44 (Estimation based on the indication of the Regulation (CE) No1272/2008.) Relative vapour density: Not applicable/Not available due to the nature/properties of the product Particle characteristics: Not applicable/Not available due to the nature/properties of the product

# 9.2 Other information

Viscosity: Not applicable/Not available due to the nature/properties of the product

Explosive properties: Not applicable/Not available due to the nature/properties of the product

Oxidizing properties: No

Dropping point: Not applicable/Not available due to the nature/properties of the product

Blink: Not applicable/Not available due to the nature/properties of the product

#### **SECTION 10: STABILITY AND REACTIVITY.**

## 10.1 Reactivity.

Contact with acids liberates toxic gas.

#### 10.2 Chemical stability.

Unstable in contact with:

- Bases.

#### 10.3 Possibility of hazardous reactions.

Warning! Do not use together with other products. May release dangerous gases (chlorine). Neutralization can occur on contact with bases.

### 10.4 Conditions to avoid.

- Avoid contact with bases.

### 10.5 Incompatible materials.

Avoid the following materials:

- Bases.

(in accordance with Regulation (EU) 2020/878)

# ctx235 SLEEPY



Version 1 Date of compilation: 17/01/2022 Page 8 of 13
Print date: 23/06/2022

#### 10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- Corrosive vapors or gases.

### **SECTION 11: TOXICOLOGICAL INFORMATION.**

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008.

Splatters in the eyes can cause irritation and reversible damage.

#### Toxicological information about the substances present in the composition.

Name		Acute toxicity			
Name	Туре	Test	Kind	Value	
		LD50	Rat	490 mg/kg [1]	
	Oral				
		[1] EPA C			
symclosene		LD50	Rabbit	>2000 mg/kg [1]	
	Dermal				
		[1] EPA C	)PP 81-2		
CAS No: 87-90-1 EC No: 201-782	-8 Inhalation				
		LD50	Rat	3500-4100 mg/kg	
		LD50	Rat	2660 mg/kg bw [1]	
	Oral				
boric acid		[1] JAMA, Journal of the American Medical Association. Vol.			
boric acid			266, 1945		
	Dermal	LD50	Rabbit	>2000 mg/kg	
		LC50	Rat	> 2 mg/l	
CAS No: 10043-35-3 EC No: 233-139-	Inhalation	LCJU	Nat	> 2 mg/1	
G. 6. No. 100 15 55 5 Ee No. 255 155		LD50	Rat	>2000 mg/kg [1]	
	Oral			3, 3, 1	
		[1] OCDE	401		
Aluminium sulfate		LD50	Rabbit	>5000 mg/kg [1]	
	Dermal				
		[1] OCDE	402		
CAS No: 10043-01-3	-0 Inhalation				
- \		•			

a) acute toxicity;

Product classified:

Acute toxicity (Oral), Category 4: Harmful if swallowed.

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation;

Product classified:

Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

(in accordance with Regulation (EU) 2020/878)

# ctx235 SLEEPY



Version 1 Date of compilation: 17/01/2022 Page 9 of 13
Print date: 23/06/2022

g) reproductive toxicity;

Based on available data, the classification criteria are not met.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3: May cause respiratory irritation.

i) STOT-repeated exposure;

Not conclusive data for classification.

i) aspiration hazard;

Not conclusive data for classification.

# 11.2 Information on other hazards.

#### **Endocrine disrupting properties**

This product does not contain components with endocrine-disrupting properties with effects on human health.

#### Other information

There is no information available on other adverse health effects.

### **SECTION 12: ECOLOGICAL INFORMATION.**

## 12.1 Toxicity.

Name		Ecotoxicity			
Name	Туре	Test	Kind	Value	
	Fish	LC50	Fish	0.32 mg/l (96h)	
symclosene	Aquatic invertebrates	LC50	Daphnia	0.21 mg/l (48h)	
CAS No: 87-90-1 EC No: 201-78	2-8 Aquatic plants				
		LC50 LC50	Fish Fish	74 mg/l (96 h) 487 mg/l (96 h) [1]	
	Fish	Boron, Mo and Coho 373. Hami to Three E	lybdenum, and Selen Salmon. Arch.Enviro	, 34-142	
boric acid	Aquatic invertebrates	Chronic To Using Bori M.A., and of Boric Ad	oxicity Test Method for c Acid. Environ.Toxic		
CAS No: 10043-35-3 EC No: 233-13	9-2 Aquatic plants				
	Fish	LC50	Fish	> 1000 mg/l (96 h)	
Aluminium sulfate	Aquatic invertebrates Aquatic plants	LC50	Daphnia	> 160 mg/l (48h)	

(in accordance with Regulation (EU) 2020/878)

# ctx235 SLEEPY



Version 1 Date of compilation: 17/01/2022 Page 10 of 13
Print date: 23/06/2022

#### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

#### 12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

#### 12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

#### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

#### 12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

#### 12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

#### **SECTION 13: DISPOSAL CONSIDERATIONS.**

#### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

### **SECTION 14: TRANSPORT INFORMATION.**

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**<u>Land</u>**: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading **Air**: Transport by plane: ICAO/IATA. Transport document: Airway bill.

(in accordance with Regulation (EU) 2020/878)

# ctx235 SLEEPY



Version 1 Date of compilation: 17/01/2022 Page 11 of 13
Print date: 23/06/2022

#### 14.1 UN number or ID number.

UN No: UN3077

#### 14.2 UN proper shipping name.

Description:

ADR/RID: UN 3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (CONTAINS SYMCLOSENE), 9, PG III, (-) IMDG: UN 3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (CONTAINS SYMCLOSENE), 9, PG III, MARINE

**POLLUTANT** 

ICAO/IATA: UN 3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (CONTAINS SYMCLOSENE), 9, PG III

#### 14.3 Transport hazard class(es).

Class(es): 9

# 14.4 Packing group.

Packing group: III

#### 14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-F

#### 14.6 Special precautions for user.

Labels: 9



Hazard number: 90 ADR LQ: 5 kg IMDG LQ: 5 kg ICAO LQ: 30 kg B

Provisions concerning carriage in bulk ADR:

VC1 Carriage in bulk in sheeted vehicles, sheeted containers or sheeted bulk containers is permitted.
VC2 Carriage in bulk in closed vehicles, closed containers or closed bulk containers is permitted.

Proceed in accordance with point 6.

# 14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

### **SECTION 15: REGULATORY INFORMATION.**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): E1,P8

(in accordance with Regulation (EU) 2020/878)

# ctx235 SLEEPY



Version 1 Date of compilation: 17/01/2022 Page 12 of 13
Print date: 23/06/2022

Information related to Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products:

Product Type	Group
Disinfectants and algaecides not intended for direct application to humans or animals	Disinfectants

Active substances	Concentration %
symclosene	
CAS No: 87-90-1	92
EC No: 201-782-8	
copper sulphate pentahydrate	
CAS No: 7758-99-8	1
EC No: 231-847-6	

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): nwg: Non-hazardous to water. (Autoclassified according to the AwSV Regulations)

#### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### **SECTION 16: OTHER INFORMATION.**

Complete text of the H phrases that appear in section 3:

H272 May intensify fire; oxidiser.
H302 Harmful if swallowed.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

H360FD May damage fertility. May damage the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

#### Classification codes:

Acute Tox. 4: Acute toxicity (Oral), Category 4

Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1 Aquatic Chronic  $\bf 1$  : Chronic effect to the aquatic environment, Category 1

Eye Dam. 1 : Serious eye damage, Category 1 Eye Irrit. 2 : Eye irritation, Category 2 Ox. Sol. 2 : Oxidising solid, Category 2 Repr. 1B : Reproductive toxicant, Category 1B

STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

# Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data Health hazards Calculation method Environmental hazards Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

(in accordance with Regulation (EU) 2020/878)

# ctx235 SLEEPY



Version 1 Date of compilation: 17/01/2022 Page 13 of 13
Print date: 23/06/2022

ADR/RID: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AwSV: Facility Regulations for handling substances that are hazardous for the water.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

EC50: Half maximal effective concentration.
PPE: Personal protection equipment.
IATA: International Air Transport Association.
ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are

not expected in the environmental compartment.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

WGK: Water hazard classes.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.