

# ASTRALPOOL - SOLID FILNET



## Cleans the inside of the sand filters

· Removes limescale and dirt deposited inside sand filters.

GRANULATED	EFFICACY	POOLS WITH SAND FILTERS	DOSAGE
300 000 000	(8h)	₩ ₩ ₩	1Kg / 10L of water

## **PROPERTIES**

Appearance	Crystalline solid
Colour	White
Density	2,12 g/cm. <sup>3</sup>
pH (solution 1%)	1,18

#### **CHARACTERISTICS**

Liquid cleaning product specially designed for the elimination of calcareous encrustations, organic residues and mineral sediments which form with time and which adhere to the surfaces of swimming pools (beaches, floating lines, steps, etc.) built in polyester and fiberglass.

It is a product designed for cleaning the pool's glass. It works by rapidly penetrating and removing stains of oxides, fumes and various dirt.

# INSTRUCTIONS FOR USE AND DOSAGE

This treatment is valid only for filters with silex or sand filtering charge.

## 1. Regular filter cleaning.

Introduce 0,5 Kgs. of ASTRALPOOL - Filnet inside the pre-filter of the pump or in the skimmer, place the filter valve in the filtration position and turn on the filter for a short time, long enough for it to reach the dissolver product inside of the filter, then stop the filter and let the ASTRALPOOL - Filnet act for approximately 1 hour and then carry out an intense countercurrent washing.





# 2. Anual filter cleaning:

Cleaning is carried out:

- A) Completely empty the water from the inside of the filter.
- B) Open the filter at the top and pour a 10% solution of ASTRALPOOL Filnet (1 Kg of product for every 10 liters of water) inside it, making sure that this solution covers the filter load as much as possible.
- C) Leave the product to react for approximately 8 hours. Close the filter and then carry out an intense washing.

