(in accordance with Regulation (EU) 2020/878)

ASTRALPOOL A

Page 1 of 11

Multi-action

Version 1 Date of compilation: 14/09/2018

Version 4 (replaces version 3) Revision date: 15/06/2022 Print date: 27/06/2022

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: Multi-action

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Desinfectant-algaecide-flocculant

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: FLUIDRA COMMERCIAL, S.A.U.

Address: Av. Alcalde Barnils, 69

City: 08174 Sant Cugat del Vallès (Barcelona) Spain

Province: Barcelona

Telephone: Tel:34 93 724 39 00 Fax:34 93 724 29 93

Fax: +34 93 713 41 11 E-mail: fds@inquide.com Web: www.astralpool.com

1.4 Emergency telephone number: +34 93 724 39 00 (Only available during office hours; Monday-Friday; 08:00-18:00)

Anti poisoning centre:

ITALY (Rome): 06/305 43 43 ITALY (Milan): 02/66 10 10 29 SPAIN: +34 91 562 04 20

FRANCE (Paris): 01 40 05 48 48 FRANCE (Tolousse): 05 61 77 74 47 FRANCE (Marseille): 04 91 75 25 25

PORTUGAL: 808 250 143

BELGIQUE (Brussel): (+34) 070 245 245

CAV accreditati: Roma +39 06 68 59 3726; Foggia +39 800 18 34 59; Napoli +39 081 54 53 333; Roma +39 06 49 97 80 00; Roma +39 06 30 54 343; Firenze +39 055 79 47 819; Pavia +39 0382 24 444; Milano +39 02 66 10 10 29; Bergamo +39 800 88

33 00; Verona +39 800 01 18 58.

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008:

Acute Tox. 4 : Harmful if swallowed. Aquatic Acute 1 : Very toxic to aquatic life.

Aquatic Chronic 1: Very toxic to aquatic life with long lasting effects.

Eye Dam. 1 : Causes serious eye damage. Ox. Sol. 2 : May intensify fire; oxidiser. STOT SE 3 : May cause respiratory irritation. STOT SE 3 : May cause drowsiness or dizziness.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:









Signal Word:

Danger

Hazard statements:

(in accordance with Regulation (EU) 2020/878)

ASTRALPOOL

Multi-action

Version 1 Date of compilation: 14/09/2018

Page 2 of 11 Print date: 27/06/2022 Version 4 (replaces version 3) Revision date: 15/06/2022

H272 May intensify fire; oxidiser. H302 Harmful if swallowed. H318 Causes serious eye damage. H335 May cause respiratory irritation.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

P370+P378 In case of fire: Use appropriate extinguishing products. Do not eat, drink or smoke when using this product. P270

P261 Avoid breathing dust.

P280 Wear protective gloves/protective clothing/eye protection.

Wash hands thoroughly after handling. P264

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P102 Keep out of reach of children.

P405 Store locked up.

Avoid release to the environment. P273

P391 Collect spillage.

P501 Dispose of contents/container in accordance with applicable regulations.

EUH statements:

FUH031 Contact with acids liberates toxic gas.

Warning! Do not use together with other products. May release dangerous gases (chlorine). EUH206

Contains:

symclosene

copper sulphate pentahydrate

Aluminium sulfate

Active substances:

symclosene, 81%;

copper sulphate pentahydrate, 2%;

2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

	Name		(*)Classification - Regulation (EC) No 1272/2008	
Identifiers		Concentrate	Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 613-031- 00-5 CAS No: 87-90-1 EC No: 201-782-8	symclosene	80 - 100 %	Acute Tox. 4 *, H302 - Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Eye Irrit. 2, H319 - Ox. Sol. 2, H272 - STOT SE 3, H335	-

(in accordance with Regulation (EU) 2020/878)

Multi-action



Version 1 Date of compilation: 14/09/2018 Page 3 of 11
Version 4 (replaces version 3) Revision date: 15/06/2022 Print date: 27/06/2022

CAS No: 10043-01-3 EC No: 233-135-0 Registration No: 01- 2119531538-36-XXXX	Aluminium sulfate	3 - 25 %	Eye Dam. 1, H318	-
Index No: 029-023- 00-4 CAS No: 7758-99-8 EC No: 231-847-6	copper sulphate pentahydrate	1 - 2.5 %	Acute Tox. 4, H302 - Aquatic Acute 1, H400 (M=10) - Aquatic Chronic 1, H410 - Eye Dam. 1, H318	-

^(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eve contact

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

Contact with eyes may cause irreversible damage.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract.

SECTION 5: FIREFIGHTING MEASURES.

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

Suitable extinguishing media: CO2 in small fires and water in large quantities (small amounts of water may aggravate the situation)

Unsuitable extinguishing media: Dry powder, Halogenated hydrocarbon, ABC powder.

5.2 Special hazards arising from the substance or mixture.

Special risks.

-Continued on next page.-

^{*} See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

(in accordance with Regulation (EU) 2020/878)

Multi-action





Page 4 of 11

Print date: 27/06/2022 **Version 4 (replaces version 3)** Revision date: 15/06/2022

Exposure to combustion or decomposition products can be harmful to your health. El producto puede provocar o facilitar la combustión de otros materiales.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

		Qualifying quantity (tonnes) for the application of	
Code	Description	Lower-tier requirements	Upper-tier requirements
P8	OXIDISING LIQUIDS AND SOLIDS	50	200
E1	ENVIRONMENTAL HAZARDS - Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1	100	200

7.3 Specific end use(s).

None in particular.

(in accordance with Regulation (EU) 2020/878)

Multi-action





ASTRALPOOI

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values. Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
	DNEL	Dermal, Chronic, Local effects	10 (mg/kg)
Alumainium autfata	(Workers)		
Aluminium sulfate	DNEL	Oral, Chronic, Systemic effects	5 (mg/kg)
CAS No: 10043-01-3 EC No: 233-135-0	(Consumers)		, , ,
EC INO: 522-122-0	DNEL	Dermal, Chronic, Systemic effects	1,8
	(Workers)	, ,	(mg/m3)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
Aluminium sulfate	Water (freshwater)	34,6 (mg/kg)
CAS No: 10043-01-3	Sediment (marine water)	3,46 (mg/kg)
EC No: 233-135-0	Soil	33,1 (mg/kg)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

CAS: 87-90-1

TLV TWA - 0.5 ppm (1.5 mg/m3) Cl gas TLV STEL - 1 ppm (3.0 mg/m3) Cl gas

CAS: 10043-01-3 TLV TWA - 2 mg/m3 (AI) 8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	Desinfectant-algaecide-flocculant		
Breathing prote	ction:		
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed			
Hand protection	l		
PPE: Characteristics:	Protective gloves against chemicals. «CE» marking, category III.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride) Breakthrough time (min.): > 480 Material thickness (mm): 0,35		

(in accordance with Regulation (EU) 2020/878)

Multi-action

Version 1 Date of compilation: 14/09/2018

Page 6 of 11 **Version 4 (replaces version 3)** Revision date: 15/06/2022 Print date: 27/06/2022



STRALPOOL

Eye protection: Protective goggles with built-in frame. PPE:

«CE» marking, category II. Eye protector with built-in frame for protection against Characteristics:

dust, smoke, fog and vapour. EN 165, EN 166, EN 167, EN 168

Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should Maintenance:

be disinfected periodically following the manufacturer's instructions.

Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, Observations:

scraping etc.

Skin protection:

CEN standards:

PPE: Chemical protective clothing

«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which Characteristics:

indicates how long it takes for the chemical to pass through the material.

CEN standards: EN 464,EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034

In order to guarantee uniform protection, follow the washing and maintenance instructions provided by Maintenance:

the manufacturer.

The protective clothing's design should facilitate correct positioning, staying in place without moving for Observations:

the period of use expected, bearing in mind environmental factors as well as any movement or position

the user might adopt while carrying out the activity.

PPF: Work footwear.

Characteristics: «CE» marking, category II. EN ISO 13287, EN 20347 CEN standards:

This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should Maintenance:

not be used by other people.

Work footwear for professional use includes protection elements aimed at protecting users against any Observations:

injury resulting from an accident

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Solid Colour: White anb blue Odour: Similar to bleach

Odour threshold: Not applicable/Not available due to the nature/properties of the product

Melting point: > 230 °C

Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: Not applicable/Not available due to the nature/properties of the product

Flammability: > 250 °C

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product Upper explosion limit: Not applicable/Not available due to the nature/properties of the product

Flash point: Not applicable/Not available due to the nature/properties of the product

Auto-ignition temperature: 1 °C

Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

pH: 1 - 3 (1%)

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product

Solubility: Not applicable/Not available due to the nature/properties of the product Hydrosolubility: Not applicable/Not available due to the nature/properties of the product Liposolubility: Not applicable/Not available due to the nature/properties of the product

Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product

Vapour pressure: Not applicable/Not available due to the nature/properties of the product Absolute density: Not applicable/Not available due to the nature/properties of the product Relative density: Not applicable/Not available due to the nature/properties of the product Relative vapour density: Not applicable/Not available due to the nature/properties of the product Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Viscosity: Not applicable/Not available due to the nature/properties of the product

Explosive properties: Not applicable/Not available due to the nature/properties of the product

Oxidizing properties: Si

Dropping point: Not applicable/Not available due to the nature/properties of the product

Blink: Not applicable/Not available due to the nature/properties of the product

(in accordance with Regulation (EU) 2020/878)

Multi-action

Version 1 Date of compilation: 14/09/2018

Page 7 of 11 Version 4 (replaces version 3) Revision date: 15/06/2022 Print date: 27/06/2022

ASTRALPOOL



10.1 Reactivity.

Contact with acids liberates toxic gas.

If the storage conditions are satisfied, does not produce dangerous reactions.

10.2 Chemical stability.

Unstable in contact with:

- Bases.

10.3 Possibility of hazardous reactions.

Warning! Do not use together with other products. May release dangerous gases (chlorine).

May intensify fire; oxidiser.

Neutralization can occur on contact with bases.

10.4 Conditions to avoid.

Avoid the following conditions:

- Contact with incompatible materials.
- Avoid contact with bases.

10.5 Incompatible materials.

Avoid the following materials:

- Flammable materials.
- Explosives materials.
- Toxic materials.
- Corrosive materials.

10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- Oxygen.
- Corrosive vapors or gases.
- Oxidizing gases or vapors.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008.

Splatters in the eyes can cause irritation and reversible damage.

Toxicological information about the substances present in the composition.

Name		Acute toxicity			
		Туре	Test	Kind	Value
		Oral	LD50	Rat	490 mg/kg [1]
			[1] EPA C	PP 81-1	
symclosene		Dermal	LD50	Rabbit	>2000 mg/kg [1]
		Dermai	[1] EPA C)PP 81-2	
CAS No: 87-90-1	EC No: 201-782-8	Inhalation			
		Ovel	LD50	Rat	>2000 mg/kg [1]
		Oral	[1] OCDE	401	
Aluminium sulfate		Downal	LD50	Rabbit	>5000 mg/kg [1]
		Dermal	[1] OCDE	402	
CAS No: 10043-01-3	EC No: 233-135-0	Inhalation			

a) acute toxicity;

Product classified:

(in accordance with Regulation (EU) 2020/878)

Multi-action

Version 1 Date of compilation: 14/09/2018

Version 4 (replaces version 3) Revision date: 15/06/2022



Page 8 of 11

Print date: 27/06/2022

Acute toxicity (Oral), Category 4: Harmful if swallowed.

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation;

Product classified:

Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3: May cause respiratory irritation.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name		Ecotoxicity			
	Name		Test	Kind	Value
		Fish	LC50	Fish	0.32 mg/l (96h)
symclosene		Aquatic invertebrates	LC50	Daphnia	0.21 mg/l (48h)
CAS No: 87-90-1	EC No: 201-782-8	Aquatic plants			
		Fish	LC50	Fish	> 1000 mg/l (96 h)
Aluminium sulfate		Aquatic invertebrates	LC50	Daphnia	> 160 mg/l (48h)
CAS No: 10043-01-3	EC No: 233-135-0	Aquatic plants			

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

(in accordance with Regulation (EU) 2020/878)

Multi-action

Version 1 Date of compilation: 14/09/2018

Page 9 of 11 Print date: 27/06/2022 Version 4 (replaces version 3) Revision date: 15/06/2022

STRALP001



No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG. Transport documentation: Bill of lading Air: Transport by plane: ICAO/IATA. Transport document: Airway bill.

14.1 UN number or ID number.

UN No: UN1479

14.2 UN proper shipping name.

Description:

ADR/RID: UN 1479, OXIDIZING SOLID, N.O.S. (CONTAINS SYMCLOSENE), 5.1, PG II, (E)

IMDG: UN 1479, OXIDIZING SOLID, N.O.S. (CONTAINS SYMCLOSENE), 5.1, PG II, MARINE POLLUTANT

ICAO/IATA: UN 1479, OXIDIZING SOLID, N.O.S. (CONTAINS SYMCLOSENE), 5.1, PG II

14.3 Transport hazard class(es).

Class(es): 5.1

14.4 Packing group.

Packing group: II

14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

Transport by ship, FEm - Emergency sheets (F - Fire, S - Spills): F-A,S-Q

(in accordance with Regulation (EU) 2020/878)

Multi-action

Version 1 Date of compilation: 14/09/2018

Page 10 of 11 Revision date: 15/06/2022 Print date: 27/06/2022 Version 4 (replaces version 3)



14.6 Special precautions for user.

Labels: 5.1



Hazard number: 50 ADR LQ: 1 kg IMDG LQ: 1 kg ICAO LQ: 2,5 kg

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Proceed in accordance with point 6.

14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): P8,E1

Information related to Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products:

Product Type	Group
Disinfectants and algaecides not intended for direct application to humans or animals	Disinfectants

Active substances	Concentration %
symclosene	
CAS No: 87-90-1	81
EC No: 201-782-8	
copper sulphate pentahydrate	
CAS No: 7758-99-8	2
EC No: 231-847-6	

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): nwg: Non-hazardous to water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H272	May intensify fire; oxidiser.
H302	Harmful if swallowed.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life

H410 Very toxic to aquatic life with long lasting effects.

(in accordance with Regulation (EU) 2020/878)

Multi-action

Version 1 Date of compilation: 14/09/2018

Version 4 (replaces version 3) Revision date: 15/06/2022



Page 11 of 11

Print date: 27/06/2022

Classification codes:

Acute Tox. 4: Acute toxicity (Oral), Category 4

Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1 Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1

Eye Dam. 1 : Serious eye damage, Category 1 Eye Irrit. 2 : Eye irritation, Category 2 Ox. Sol. 2 : Oxidising solid, Category 2

STOT SE 3: Specific target organ toxicity following a single exposure, Category 3

Changes regarding to the previous version:

- Modification of specific hazards (SECTION 2.3).
- Modification in the firefighting measures (SECTION 5.2).
- Modifications in the accidental release measures (SECTION 6.1).
- Modifications in the accidental release measures (SECTION 6.2).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Change in the hazard classification (SECTION 11.1).
- Modification of the classification ADR/IMDG/ICAO/IATA/RID (SECTION 14).
- Addition of abbreviations and acronyms (SECTION 16).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data Health hazards Calculation method Environmental hazards Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR/RID: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AwSV: Facility Regulations for handling substances that are hazardous for the water.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

EC50: Half maximal effective concentration.
 PPE: Personal protection equipment.
 IATA: International Air Transport Association.
 ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are

not expected in the environmental compartment.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

WGK: Water hazard classes.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.