

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



ctx342 Multiaction 5

Version 1 Date of compilation: 23/06/2022

Page 1 of 12
Print date: 01/07/2022

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: ctx342 Multiaction 5

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Desinfectant-algaecide-flocculant

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **FLUIDRA COMERCIAL ESPAÑA**
Address: Av. Alcalde Barnils, 69
City: 08174 Sant Cugat del Vallès
Province: Barcelona (España)
Telephone: telf: 902 42 32 22
Fax: +34 93 713 41 11
E-mail: fds@inquide.com
Web: www.ctxprofessional.com

1.4 Emergency telephone number: (Available 24 hours)

Anti poisoning centre:

ITALY (Rome): 06/305 43 43

ITALY (Milan): 02/66 10 10 29

SPAIN: +34 91 562 04 20

FRANCE (Paris): 01 40 05 48 48 FRANCE (Toulouse): 05 61 77 74 47 FRANCE (Marseille): 04 91 75 25 25

PORTUGAL: 808 250 143

BELGIQUE (Brussel): (+34) 070 245 245

CAV accreditati: Roma +39 06 68 59 3726; Foggia +39 800 18 34 59; Napoli +39 081 54 53 333; Roma +39 06 49 97 80 00;

Roma +39 06 30 54 343; Firenze +39 055 79 47 819; Pavia +39 0382 24 444; Milano +39 02 66 10 10 29; Bergamo +39 800 88 33 00; Verona +39 800 01 18 58.

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008:

Acute Tox. 4 : Harmful if swallowed.

Aquatic Acute 1 : Very toxic to aquatic life.

Aquatic Chronic 1 : Very toxic to aquatic life with long lasting effects.

Eye Dam. 1 : Causes serious eye damage.

Ox. Sol. 2 : May intensify fire; oxidiser.

STOT SE 3 : May cause respiratory irritation.

STOT SE 3 : May cause drowsiness or dizziness.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



ctx342 Multiaction 5

Version 1 Date of compilation: 23/06/2022

Page 2 of 12
Print date: 01/07/2022



Signal Word:

Danger

Hazard statements:

H272 May intensify fire; oxidiser.
H302 Harmful if swallowed.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P370+P378 In case of fire: Use appropriate extinguishing products.
P270 Do not eat, drink or smoke when using this product.
P261 Avoid breathing dust.
P280 Wear protective gloves/protective clothing/eye protection.
P264 Wash hands thoroughly after handling.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P102 Keep out of reach of children.
P405 Store locked up.
P273 Avoid release to the environment.
P391 Collect spillage.
P501 Dispose of contents/container in accordance with applicable regulations.

EUH statements:

EUH031 Contact with acids liberates toxic gas.
EUH206 Warning! Do not use together with other products. May release dangerous gases (chlorine).

Contains:

symclosene
Aluminium sulfate

Active substances:

symclosene, 80%;

2.3 Other hazards.

The mixture does not contain substances classified as PBT.
The mixture does not contain substances classified as vPvB.
The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008
-------------	------	-------------	---

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



ctx342 Multiaction 5

Version 1 Date of compilation: 23/06/2022

Page 3 of 12
Print date: 01/07/2022

			Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 613-031-00-5 CAS No: 87-90-1 EC No: 201-782-8	symclosene	30 - 100 %	Acute Tox. 4 *, H302 - Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Eye Irrit. 2, H319 - Ox. Sol. 2, H272 - STOT SE 3, H335	-
Index No: 005-007-00-2 CAS No: 10043-35-3 EC No: 233-139-2 Registration No: 01-2119486683-25-XXXX	[5] boric acid	0.1 - 0.29 %	Repr. 1B, H360FD	Repr. 1B, H360FD: C ≥ 5,5 %
CAS No: 10043-01-3 EC No: 233-135-0 Registration No: 01-2119531538-36-XXXX	Aluminium sulfate	3 - 10 %	Eye Dam. 1, H318	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[2] Substance with a national workplace exposure limit (see section 8.1).

[5] Substance included in the list established under Article 59, paragraph 1, REACH (Candidate substance).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

Contact with eyes may cause irreversible damage.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



ctx342 Multiaction 5

Version 1 Date of compilation: 23/06/2022

Page 4 of 12
Print date: 01/07/2022

SECTION 5: FIREFIGHTING MEASURES.

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

Suitable extinguishing media: CO₂ in small fires and water in large quantities (small amounts of water may aggravate the situation)

Unsuitable extinguishing media: Dry powder, Halogenated hydrocarbon, ABC powder.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health. El producto puede provocar o facilitar la combustión de otros materiales.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



ctx342 Multiaction 5

Version 1 Date of compilation: 23/06/2022

Page 5 of 12
Print date: 01/07/2022

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
P8	OXIDISING LIQUIDS AND SOLIDS	50	200
E1	ENVIRONMENTAL HAZARDS - Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1	100	200

7.3 Specific end use(s).

None in particular.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
boric acid CAS No: 10043-35-3 EC No: 233-139-2	DNEL (Workers)	Inhalation, Chronic, Systemic effects	8,3 (mg/m ³)
Aluminium sulfate CAS No: 10043-01-3 EC No: 233-135-0	DNEL (Workers)	Dermal, Chronic, Local effects	10 (mg/kg)
	DNEL (Consumers)	Oral, Chronic, Systemic effects	5 (mg/kg)
	DNEL (Workers)	Dermal, Chronic, Systemic effects	1,8 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
Aluminium sulfate CAS No: 10043-01-3 EC No: 233-135-0	Water (freshwater)	34,6 (mg/kg)
	Sediment (marine water)	3,46 (mg/kg)
	Soil	33,1 (mg/kg)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

CAS: 87-90-1

TLV TWA - 0.5 ppm (1.5 mg/m³) Cl gas

TLV STEL - 1 ppm (3.0 mg/m³) Cl gas

CAS: 10043-01-3

TLV TWA - 2 mg/m³ (Al)

8.2 Exposure controls.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



ctx342 Multiaction 5

Version 1 Date of compilation: 23/06/2022

Page 6 of 12
Print date: 01/07/2022

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	Desinfectant-algaecide-flocculant
Breathing protection:	
If the recommended technical measures are observed, no individual protection equipment is necessary.	
Hand protection:	
If the product is handled correctly, no individual protection equipment is necessary.	
Eye protection:	
If the product is handled correctly, no individual protection equipment is necessary.	
Skin protection:	
PPE:	Work footwear.
Characteristics:	«CE» marking, category II.
CEN standards:	EN ISO 13287, EN 20347
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Solid

Colour: White

Odour: Of chlorine

Odour threshold: Not applicable/Not available due to the nature/properties of the product

Melting point: > 230 °C

Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: Not applicable/Not available due to the nature/properties of the product

Flammability: > 250 °C

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product

Upper explosion limit: Not applicable/Not available due to the nature/properties of the product

Flash point: Not applicable/Not available due to the nature/properties of the product

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product

Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

pH: 2,1 - 3 (1%)

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product

Solubility: Not applicable/Not available due to the nature/properties of the product

Hydrosolubility: Not applicable/Not available due to the nature/properties of the product

Liposolubility: Not applicable/Not available due to the nature/properties of the product

Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product

Vapour pressure: Not applicable/Not available due to the nature/properties of the product

Absolute density: Not applicable/Not available due to the nature/properties of the product

Relative density: 1,44 (Estimation based on the indication of the Regulation (CE) N°1272/2008.)

Relative vapour density: Not applicable/Not available due to the nature/properties of the product

Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Viscosity: Not applicable/Not available due to the nature/properties of the product

Explosive properties: Not applicable/Not available due to the nature/properties of the product

Oxidizing properties: Si

Dropping point: Not applicable/Not available due to the nature/properties of the product

Blink: Not applicable/Not available due to the nature/properties of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



ctx342 Multiaction 5

Version 1 Date of compilation: 23/06/2022

Page 7 of 12
Print date: 01/07/2022

Contact with acids liberates toxic gas.
If the storage conditions are satisfied, does not produce dangerous reactions.

10.2 Chemical stability.

Unstable in contact with:
- Bases.

10.3 Possibility of hazardous reactions.

Warning! Do not use together with other products. May release dangerous gases (chlorine).
May intensify fire; oxidiser.
Neutralization can occur on contact with bases.

10.4 Conditions to avoid.

Avoid the following conditions:
- Contact with incompatible materials.
- Avoid contact with bases.

10.5 Incompatible materials.

Avoid the following materials:
- Bases.
- Flammable materials.
- Explosives materials.
- Toxic materials.
- Corrosive materials.

10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:
- Oxygen.
- Corrosive vapors or gases.
- Oxidizing gases or vapors.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

11.1 Information on hazard classes as defined in Regulation (EC) N° 1272/2008.

Splatters in the eyes can cause irritation and reversible damage.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
symclosene CAS No: 87-90-1 EC No: 201-782-8	Oral	LD50	Rat	490 mg/kg [1]
		[1] EPA OPP 81-1		
	Dermal	LD50	Rabbit	>2000 mg/kg [1]
		[1] EPA OPP 81-2		
	Inhalation			
boric acid CAS No: 10043-35-3 EC No: 233-139-2	Oral	LD50	Rat	3500-4100 mg/kg
		LD50	Rat	2660 mg/kg bw [1]
		[1] JAMA, Journal of the American Medical Association. Vol. 128, Pg. 266, 1945		
	Dermal	LD50	Rabbit	>2000 mg/kg
	Inhalation	LC50	Rat	> 2 mg/l

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



ctx342 Multiaction 5

Version 1 Date of compilation: 23/06/2022

Page 8 of 12
Print date: 01/07/2022

Aluminium sulfate	Oral	LD50 Rat >2000 mg/kg [1] [1] OCDE 401
	Dermal	LD50 Rabbit >5000 mg/kg [1] [1] OCDE 402
	Inhalation	

CAS No: 10043-01-3 EC No: 233-135-0

a) acute toxicity;

Product classified:

Acute toxicity (Oral), Category 4: Harmful if swallowed.

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation;

Product classified:

Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Based on available data, the classification criteria are not met.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3: May cause respiratory irritation.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
symclosene	Fish	LC50	Fish	0.32 mg/l (96h)
	Aquatic invertebrates	LC50	Daphnia	0.21 mg/l (48h)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



ctx342 Multiaction 5

Version 1 Date of compilation: 23/06/2022

Page 9 of 12
Print date: 01/07/2022

CAS No: 87-90-1	EC No: 201-782-8	Aquatic plants	
boric acid		Fish	LC50 Fish 74 mg/l (96 h) LC50 Fish 487 mg/l (96 h) [1] [1] Hamilton, S.J., and K.J. Buhl 1990. Acute Toxicity of Boron, Molybdenum, and Selenium to Fry of Chinook Salmon and Coho Salmon. Arch.Environ.Contam.Toxicol. 19(3):366-373. Hamilton, S.J. 1995. Hazard Assessment of Inorganics to Three Endangered Fish in the Green River, Utah. Ecotoxicol.Environ.Saf. 30(2):134-142
		Aquatic invertebrates	LC50 Daphnia 133 mg/l (48 h) LC50 Crustacean 180 mg/l (48 h) [1] [1] Gersich, F.M. 1984. Evaluation of a Static Renewal Chronic Toxicity Test Method for Daphnia magna Straus Using Boric Acid. Environ.Toxicol.Chem. 3(1):89-94. Lewis, M.A., and L.C. Valentine 1981. Acute and Chronic Toxicities of Boric Acid to Daphnia magna Straus. Bull.Environ.Contam.Toxicol. 27(3):309-315
		Aquatic plants	
CAS No: 10043-35-3	EC No: 233-139-2	Aquatic plants	
Aluminium sulfate		Fish	LC50 Fish > 1000 mg/l (96 h)
		Aquatic invertebrates	LC50 Daphnia > 160 mg/l (48h)
		Aquatic plants	
CAS No: 10043-01-3	EC No: 233-135-0	Aquatic plants	

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.
No information is available on the degradability of the substances present.
No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.
Follow the provisions of Directive 2008/98/EC regarding waste management.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



ctx342 Multiaction 5

Version 1 Date of compilation: 23/06/2022

Page 10 of 12
Print date: 01/07/2022

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

14.1 UN number or ID number.

UN No: UN1479

14.2 UN proper shipping name.

Description:

ADR/RID: UN 1479, OXIDIZING SOLID, N.O.S. (CONTAINS SYMCLOSENE), 5.1, PG II, (E)

IMDG: UN 1479, OXIDIZING SOLID, N.O.S. (CONTAINS SYMCLOSENE), 5.1, PG II, MARINE POLLUTANT

ICAO/IATA: UN 1479, OXIDIZING SOLID, N.O.S. (CONTAINS SYMCLOSENE), 5.1, PG II

14.3 Transport hazard class(es).

Class(es): 5.1

14.4 Packing group.

Packing group: II

14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-Q

14.6 Special precautions for user.

Labels: 5.1



Hazard number: 50

ADR LQ: 1 kg

IMDG LQ: 1 kg

ICAO LQ: 2,5 kg

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Proceed in accordance with point 6.

14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



ctx342 Multiaction 5

Version 1 Date of compilation: 23/06/2022

Page 11 of 12
Print date: 01/07/2022

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): P8,E1

Information related to Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products:

Product Type	Group
Disinfectants and algacides not intended for direct application to humans or animals	Disinfectants

Active substances	Concentration %
symclosene CAS No: 87-90-1 EC No: 201-782-8	80

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): WGK 2: Hazardous to water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H272	May intensify fire; oxidiser.
H302	Harmful if swallowed.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H360FD	May damage fertility. May damage the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 : Acute toxicity (Oral), Category 4
Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1
Eye Dam. 1 : Serious eye damage, Category 1
Eye Irrit. 2 : Eye irritation, Category 2
Ox. Sol. 2 : Oxidising solid, Category 2
Repr. 1B : Reproductive toxicant, Category 1B
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



ctx342 Multiaction 5

Version 1 Date of compilation: 23/06/2022

Page 12 of 12
Print date: 01/07/2022

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR/RID: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AwSV: Facility Regulations for handling substances that are hazardous for the water.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

EC50: Half maximal effective concentration.

PPE: Personal protection equipment.

IATA: International Air Transport Association.

ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

WGK: Water hazard classes.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.