TAXIWAY LIGHTING

ETE-CB

Incandescent Elevated Taxiway Edge Light

MEDIUM-INTENSITY, CLAMP BAND



44C1081 - X X XX

Compliance with Standards

FAA: L-861T AC 150/5345-46 (Current Edition). ETL Certified.

Uses

FAA L-861T

Used to delineate the edges of airport taxiways.

Features

- Multiple lamp wattages and types (6.6 A quartz or 6.6 A incandescent) available
- Single-latch, stainless steel clamping band allows easy removal of lens for lamp changes
- Lamp Life: Rated at 1,000 hours at 6.6 A
- A gasket is used between the lens and the head assembly to form a tight seal
- Three screws allow a 4° leveling adjustment of the fixture after installation
- Fixture comes standard with a 1.5-inch coupling, but is available with a 2-inch coupling and in alternative thread patterns
- Fixture uses aluminum head assembly, stainless steel hard- ware, and is protected with aviation yellow enamel paint

Operating Conditions

Temperature: -40 °F to +131 °F (-40 °C to +55 °C)

Wind: Withstands wind velocities up to 300 mph (480 kph)

Ordering Code

Lamp

1 = 30 W/6.6 A Incandescent²

 $2 = 45 \text{ W}/6.6 \text{ A Incandescent}^2$

3 = 25 W/120 VAC, Incandescent²

5 = 30 W/6.6 A Quartz (ETL Certified)

 $6 = 45 \text{ W}/6.6 \text{ A Quartz}^2$

7 = No Lamp, Incandescent Socket

8 = No Lamp, Quartz Socket

Lens Color

 $0 = No lens^1$

5 = Omnidirectional Blue (ETL Certified)³

Fixture Height

11 = 14 in (35.6 cm) with 1.5" coupling, 12 TPI

22 = 24 in (61.0 cm) with 1.5" coupling, 12 TPI

33 = 30 in (76.2 cm) with 1.5" coupling, 12 TPI

44 = 20 in (50.8 cm) with 1.5" coupling, 12 TPI

 $1A = 14 \text{ in } (35.6 \text{ cm}) \text{ with } 2'' \text{ coupling, } 11 \text{ TPI}^4$

Notes

- No lens option normally used as spare part. Specify and order lens separately.
- ² Lamp not certified
- 3 30 W Quartz
- ⁴ Normally used in metric applications

Packaging

Assembled Fixtures	Dimensions of Cartons		Indiv.
	Individual in (cm)	9/Box in (cm)	Weight
14-inch OAH	6.5 × 6.5 × 20.5	19.5 × 19.5 × 20.5	5 lb
	(17 × 17 × 52)	(50 × 50 × 52)	2.3 kg
24-inch OAH	6.5 × 6.5 × 31	19.5 × 19.5 × 31	6.25 lb
	(17 × 17 × 79)	(50 × 50 × 79)	2.8 kg
30-inch OAH	6.5 × 6.5 × 37	19.5 × 19.5 × 37	7 lb
	(17 × 17 × 94)	(50 × 50 × 94)	3.2 kg

www.adbsafegate.com



3063 Rev. A 1