

406 Crossrib Sof-Tred™

Dyna-Shield™ layer with side-to-side wide ribs



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Linear Lengths

406 Crossrib Sof-Tred™

Exceptional worker comfort due to 12.7 mm thick specially formulated compound. Protective layer of exclusive Dyna-Shield™ extends service life by 50% compared to regular microcellular vinyl.

- Available with yellow borders along sides to comply with OSHA code 1910-144
- All 4 sides are bevelled and sealed to minimize tripping hazards
- Side-to-side wide ribs provide traction and easy to sweep clean

Recommended use

- Dry Areas
- For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
- Medium duty

Colors:

- Black/Yellow
- Grey

Sizes:

- 60cm x 91cm
- 91cm x 150cm
- 122cm x linm
- 60cm x linm
- 91cm x linm
- 122cm x 18.3m
- 60cm x 18.3m
- 91cm x 18.3m



WEAR RESISTANCE

SLIP RESISTANCE

ANTI-FATIGUE

Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Linear Lengths Crossrib Sof-Tred™

General

Brand	Notrax
Category	Dry Areas Linear Lengths
Product Number	406
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Crossrib Sof-Tred™
Recommended use	For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
Shipping Location	Barendrecht 2992SB, The Netherlands, Moselle, MS 39459, United States
Type	Dry Areas - Dyna Shield™
Update trigger	20210310-1301
Usage Intensity	Medium duty

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Reach US	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Sustainability	Recyclable material
Warranty	1

Tests

Abrasion Resistance 1000	2.02%
Abrasion Resistance 500	1.7%
Compression Deflection 1.4	0.71 cm
Compression Deflection 2.8	0.84 cm
Elongation	144%
Fire rating US	Pass
Hardness	25 Shore A
Slip Rating	R10
Coefficient Friction Dry	1.10
Surface Flammability	Pass
Tear Strength	10.5 lb

Technical Specifications

Application	Industrial Environments
Backing	Microcellular vinyl
Breaking Load	22.1 lb
Edges	Bevelled edges on all sides
Material	Microcellular vinyl
Material Group	Vinyl
Process	Foaming

Crossrib Sof-Tred™ Grey

Art. nr.	Dimension (cm)	Weight (kg)	Height (cm)
406R0048GY	122cm x 18.3m	86	1.27
406R0036GY	91cm x 18.3m	64	1.27
406S0035GY	91cm x 150cm	5.3	1.27
406S0023GY	60cm x 91cm	2.1	1.27
406R0024GY	60cm x 18.3m	43	1.27
406C0024GY	60cm x linm	2.3	1.27
406C0048GY	122cm x linm	4.7	1.27
406C0036GY	91cm x linm	3.5	1.27

Crossrib Sof-Tred™ Black/Yellow

Art. nr.	Dimension (cm)	Weight (kg)	Height (cm)
406R0048BY	122cm x 18.3m	86	1.27
406R0036BY	91cm x 18.3m	64	1.27
406R0024BY	60cm x 18.3m	43	1.27
406C0048BY	122cm x linm	4.7	1.27
406C0036BY	91cm x linm	3.5	1.27
406C0024BY	60cm x linm	2.3	1.27
406S0023BY	60cm x 91cm	2.1	1.27
406S0035BY	91cm x 150cm	5.3	1.27