

832 Switchboard Matting™ Class 4

Class 4 insulation matting



Ergonomic, Anti-fatigue & Safety Matting - Switchboard Matting

832 Switchboard Matting™ Class 4

Insulating matting prevents workers from being “grounded” and provides safety in case of electrical shock. The corrugated saw-tooth top surface increases traction and is easy to sweep clean.

- Each square inch of matting is tested in conformance with ANSI/ASTM D-178 specifications
- The corrugated saw-tooth top surface increases traction and is easy to sweep clean
- Must be replaced every 12 months for optimum safety
- Recommended maximum usage: 36,000 V

Recommended use

- Dry Areas
- Around electric sub-stations, transformers and switches, electrical panels, engine and generator rooms
- Heavy duty

Colors:

- Black

Sizes:

- 91cm x 150cm
- 91cm x 1inm
- 91cm x 9.14m



Ergonomic, Anti-fatigue & Safety Matting - Switchboard Matting

Switchboard Matting™ Class 4

General

Brand	Notrax
Category	Switchboard Matting
Product Number	832
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Switchboard Matting™ Class 4
Recommended use	Around electric sub-stations, transformers and switches, electrical panels, engine and generator rooms
Shipping Location	Barendrecht 2992SB, The Netherlands
Type	Industrial Specialties - Electrical Protective Matting
Update trigger	20210310-1301
Usage Intensity	Heavy duty

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Warranty	1

Tests

Elongation	270%
Hardness	91 Shore A
Surface Flammability	Pass

Technical Specifications

Application	Industrial Environments
Edges	No borders
Material	PVC (DOP free)
Material Group	PVC
Process	Calendering
Voltage Class	4
Voltage Maximum	40000
Voltage Recommended	36000

Switchboard Matting™ Class 4 Black

Art. nr.	Dimension (cm)	Weight (kg)	Height (cm)
832S0035BL	91cm x 150cm	12.8	1.22
832C0036BL	91cm x linm	8.6	1.22
832R0330BL	91cm x 9.14m	85.5	1.22